

Tehnički list za artikl: AC20606031

Empty field Modul 2500TT, 1 door IP31, H=2000 W=600 D=600mm

sheet steel, RAL7035, four-point rod lock with push-pull handle



Tehnički podaci

Neto širina (mm)	600,00
Neto visina (mm)	2.000,00
Neto dubina (mm)	600,00
Neto masa (kg)	105,80
Min. temperatura okoline (°C)	-10
Maks. temperatura okoline (°C)	60
IP stupanj zaštite	IP31
Klasa zaštite	I
Materijal	Čelični lim
Boja	RAL 7035 (svijetlo siva)
Širina (mm)	600
Visina (mm)	2000
Dubina (mm)	600
Debljina stijenke tijela (mm)	1,50
Debljina stijenke vrata (mm)	2
Opteretivost vrata (kg)	100
Broj vrata	1

Tehnički podaci - nastavak

Dodatni pribor

ACSOT062--;ACSOB062--;ACPMP0806--;ACPMP0604--;AC2500BBW-;AC2500BBH-;AC2500BBD-;AC2500BH1-;AC2500BH2-;AC2500PE-;ACSOT062--;ACSOB062--;ACCLH600--;ACCLC400--;ACCLF200--;ACCAB600--;ACLE9301--;IL900415-F;ACTW2006--;ACSPDG01--;ASDRA400--

Tablica artikla

OPIS	KAT. BROJ
Empty field Modul 2500TT, 1 door IP31, H=2000 W=600 D=600mm sheet steel, RAL7035, four-point rod lock with push-pull handle	AC20606031
Dodatni pribor	
Podnožje prema dubini AC ormara 600x200mm, RAL9005 Isporuka sadrži lijevi i desni element (par, prema dubini ormara) te 4 (predmontirana) kutna elementa	ACSOT062
Podnožje prema širini AC ormara 600x200mm, RAL9005 Isporuka sadrži prednji i stražnji element podnožja (par, prema širini ormara)	ACSOB062
Parcijalna mont.ploča za razdj. AC/KC, dimenzija 800x600 za ormare dubine 600mm, mogućnost montaže horizontalno i vertikalno	ACPMP0806
Parcijalna mont.ploča za razdj. AC/KC, dimenzija 600x400 za ormare dubine 400mm, mogućnost montaže horizontalno i vertikalno	ACPMP0604
Busbar holder, horizontal element (PU=6 Pieces)	AC2500BBW
Busbar holder, vertical element H=100mm (PU=6 Pieces)	AC2500BBH
Busbar holder spacer 9mm (PU=24 Pieces)	AC2500BBD
L-shaped mounting bracket for busbar holder	AC2500BH1
T-shaped mounting bracket for busbar holder	AC2500BH2
Z-shaped mounting bracket for PE rail	AC2500PE
Podnožje prema dubini AC ormara 600x200mm, RAL9005 Isporuka sadrži lijevi i desni element (par, prema dubini ormara) te 4 (predmontirana) kutna elementa	ACSOT062
Podnožje prema širini AC ormara 600x200mm, RAL9005 Isporuka sadrži prednji i stražnji element podnožja (par, prema širini ormara)	ACSOB062
Montažni profil za velike terete (par) L=600mm sa montažnim priborom	ACCLH600
Montažni profil "klik" (par) L=400mm s priborom za montažu	ACCLC400
Montažni profil (par) L=2000 mm s priborom za montažu	ACCLF200

Tablica artikla

OPIS	KAT. BROJ
Dodatni pribor	
Držač kabela (par) za ormare širine 600 mm	
Šine za sigurno fiksiranje dolaznih kabela u AC/KC ormare. Montaža: iznad donje ploče na nižem bočnom profilu okvira ormara ili ACCAB600 na montažnoj ploči. Pakiranje: 1 par s montažnim materijalom.	
Transportne ušice M12 za AC, KC, AT, KT ormare, 4 komada za podizanje kompaktnog samostojećeg ili jednog serijskog ormara	ACLE9301
Prirubnica za uvod kabela, Š=410mm does not correspond to degree of protection IP2x-C	IL900415-F
Odjelna stranica za AC ormare, 2000x600mm (ŠxV)	ACTW2006
Brтва od polietilena PE-01, IP55	ACSPDG01
Spremnik za dokumentaciju, samoljepljivi, A4	ASDRA400