



Tehnički list za artikl: AC20802N15

Outgoing field Modul 2500TT, 1 door IP31, H2000 W800 D600mm

for 6 pcs. NH Fuse switches size 1-3 (not included)



Tehnički podaci

Neto širina (mm)	800,00
Neto visina (mm)	2.000,00
Neto dubina (mm)	600,00
Neto masa (kg)	180,00
Min. temperatura okoline (°C)	-10
Maks. temperatura okoline (°C)	60
IP stupanj zaštite	IP31

Tehnički podaci - nastavak

Klasa zaštite	I
Materijal	Čelični lim
Boja	RAL 7035 (svijetlo siva)
Širina (mm)	800
Visina (mm)	2000
Dubina (mm)	600
Debljina stijenke tijela (mm)	1,50
Debljina stijenke vrata (mm)	2
Opteretivost vrata (kg)	100
Broj vrata	1
Dodatni pribor	ACSOT062--;ACSOB082--;ACPMPO804--;ACCLF200--;ACLE9301--;L900418-F;ACTW2006--;ACSPDG01--

Tablica artikla

OPIS	MASA BAKRA (kg/km)	KAT. BROJ
Outgoing field Modul 2500TT, 1 door IP31, H2000 W800 D600mm for 6 pcs. NH Fuse switches size 1-3 (not included)		AC20802N15
Potrebni pribor		
Bočne stranice (par) za AC ormara, 2000x600mm (ŠxV), RAL7035 isporuka u paru (lijeva i desna bočna stranica)		ACSW2006
Set za povezivanje ormara iznutra sa 4 kutnika, 6 spojnika i montažnim priborom		ACCCM040
Busbar end cover		AC2500BBC
Copper mounting kit for field connection, Modul 2500TT PU=8 pieces 80x10mm (main busbar/neutral bar) and 1 piece 100x10mm (earthing bar)		AC2500CUMB
Copper mounting kit for starter and end bays, Modul 2500TT PU=8 pieces half 80x10mm slats		AC2500CUEB
NV rastavna pruga vel.00 160A, 3P, M8, sustav 100mm NH-Leiste, für 100mm-Sammelschienenensystem, M8, 3-polig	420	ISA05261
NV rastavljačka pruga ARROW BLACK vel 1, 3P, 250A 185mm sabirnički sustav, M10, varijanta za integraciju strujnog transformatora	1788	ISA05361
NV rastavljačka pruga ARROW BLACK vel 2, 3P, 400A 185mm sabirnički sustav, M12, varijanta za integraciju strujnog transformatora	2068	ISA05362
NV rastavljačka pruga ARROW BLACK vel 3, 3P, 600A 185mm sabirnički sustav, M12, varijanta za integraciju strujnog transformatora	2707	ISA05363

Tablica artikla

OPIS	MASA BAKRA (kg/km)	KAT. BROJ
Potrebni pribor		
HRC-in-line-fuse ARROW BLACK size 1, 3-pole, 250A, V-term. Version to integrate current transformers, 185mm busbar system, V box terminal 25-300mm ²	1895	ISA05371
HRC-in-line-fuse ARROW BLACK size 2, 3-pole, 400A, V-term. Version to integrate current transformers, 185mm busbar system, V box terminal 25-300mm ²	2181	ISA05372
HRC-in-line-fuse ARROW BLACK size 3, 3-pole, 630A, V-term. Version to integrate current transformers, 185mm busbar system, V box terminal 25-300mm ²	2820	ISA05373
Dodatni pribor		
Podnožje prema dubini AC ormara 600x200mm, RAL9005 Isporuka sadrži lijevi i desni element (par, prema dubini ormara) te 4 (predmontirana) kutna elementa		ACSOT062
Podnožje prema širini AC ormara 800x200mm, RAL9005 Isporuka sadrži prednji i stražnji element podnožja (par, prema širini ormara)		ACSOB082
Parcijalna mont.ploča za razdj. AC/KC, dimenzija 800x400 za ormare dubine 400mm, mogućnost montaže horizontalno i vertikalno		ACPMPO804
Montažni profil (par) L=2000 mm s priborom za montažu		ACCLF200
Transportne ušice M12 za AC, KC, AT, KT ormare, 4 komada za podizanje kompaktnog samostojećeg ili jednog serijskog ormara		ACLE9301
Prirubnica za uvod kabela, Š=620mm does not correspond to degree of protection IP2x-C		IL900418-F
Odjelna stranica za AC ormare, 2000x600mm (ŠxV)		ACTW2006
Brтва od polietilena PE-01, IP55		ACSPDG01