

Tehnički list za artikl: BK090204--

Nazidni razdjelnik, 2-redni, 36 modula, prozirna vrata, IP65

2-redni, 18 modula u jednom redu, 464x432x160mm (VxŠxD), UV postojan i otporan na vremenske uvjete, 1000V DC, IK08, materijal ABS, 1 x N sabirnica (10x10mm² + 10x16mm²), 1 x PE sabirnica (10x10mm² + 10x16mm²)



SCHRACK-Info

- Nazidni razdjelnik s prozirnim vratima
- Zatvaranje: mehanizam na pritisak, mogućnost ugradnje male cilindar brave
- Uvod kabela kroz gumene membrane
- Sadrži N/PE sabirnice
- Bez halogena
- Klasa zaštite II

- UV postojan
- Nazivni napon: 400V AC, 1000V DC
- Temperatura okoline: -25°C do +85°C
- Materijal: ABS
- Stupanj zaštite: IP65
- Otpornost na udarce: IK08
- Boja: RAL7035 (svijetlo-siva)

Tehnički podaci

Neto širina (mm)	432,00
Neto visina (mm)	464,00
Neto dubina (mm)	160,00
Neto masa (kg)	3,96
EAN	9004840817942
Disipacija snage (W)	-35,00
Min. temperatura okoline (°C)	-25
Maks. temperatura okoline (°C)	85

Tablica artikla

OPIS	KAT. BROJ
Nazidni razdjelnik, 2-redni, 36 modula, prozirna vrata, IP65	
2-redni, 18 modula u jednom redu, 464x432x160mm (VxŠxD), UV postojan i otporan na vremenske uvjete, 1000V DC, IK08, materijal ABS, 1 x N sabirnica (10x10mm ² + 10x16mm ²), 1 x PE sabirnica (10x10mm ² + 10x16mm ²)	BK090204
Dodatni pribor	
Polucilindar, brava za BK09, IP65 za nazidne razdjelnike	BK090097