

Tehnički list za artikl: DTT166010B

Serverski ormar S-RACK, Š600 V855 D1000, 19", 16U

800kg nosivost, prednja vrata perforirana jednostruka, zadnja vrata perforirana dvostruka, RAL9005 crni



SCHRACK-Info

Server cabinets are mainly used in data centers and server rooms where an increased load is required and heavy installations such as servers, UPS, etc., have to be installed.

- **Material thickness:**
 - Top and bottom chassis: 1.5mm
 - Corner profile: 1.2mm
 - Rails: 1.5mm
 - Front metal door perforated, full width: 80%
 - Rear door perforated double-wing: 80%
 - Side panel: 0.8mm
- **Colour:**
 - RAL9005 (black)
- **Height:** 16U
- **Width:** 600mm
- **Depth:** 1.000mm
- **Maximum load:** with even distribution: 800kg
- **Degree of protection:** IP20

- **Dismountability:** The individual parts of the cabinet are screwed. The enclosure is delivered assembled and can be partially or completely disassembled for transport to places that are difficult to access.
- **Frontdoor:** Metal door perforated full width including comfort swing handle with lock and keys. A conversion kit for half cylinders (DTZLOCK02) is optionally available. External hinge system allows door opening angle of up to 180°. Door hinged on the right. Conversion to left hinged door is possible.
- **Side and back doors:** Removable side and back doors with lock and keys.
- **Cable entry options:** In roof and floor. Fitted with plastic blank covers. The floor also accommodates a large break-out blank plate which can be easily removed for cable entry. Brush entry DTBB optionally available.
- **Cooling:** Passive cooling through heat exchange with the outside area. Ventilation slots on the roof are prepared for cooling. Active cooling through optional DTLT fan units.
- **Rails:** 19" rails (4 pieces), depth adjustable, U markings included
- **Accessories:** Numerous accessories (base sets, fans, shelves, cable management, doors, etc.) available
- **Earthing:** Earthing set is included
- **Levelling Feet:** Levelling Feet are included
- **Included mounting material:** 16 pieces cage nuts, screws and washers
- **Delivery:** Enclosure is delivered fully assembled on a throw-away pallet.

Tehnički podaci

Neto širina (mm)	600,00
Neto visina (mm)	855,00
Neto dubina (mm)	1.000,00
Neto masa (kg)	39,70
EAN	9004840691702
Min. temperatura okoline (°C)	5
Maks. temperatura okoline (°C)	40
Visinska jedinica	16
Boja	RAL 9005 (crna)
IP stupanj zaštite	IP20
Maksimalno opterećenje (kg)	800
Serijski broj	S-RACK

Tablica artikla

OPIS	KAT. BROJ
Serverski ormar S-RACK, Š600 V855 D1000, 19", 16U	DTT166010B
800kg nosivost, prednja vrata perforirana jednostruka, zadnja vrata perforirana dvostruka, RAL9005 crni	
Dodatni pribor	
	DTOT10601B

Tablica artikla

OPIS	KAT. BROJ
Dodatni pribor	
Krovna vent. jed., 2 vent. za DT/DTW, analog. term., RAL9005 Installation from outside of enclosure, for freestanding and wallmount enclosures	DTLTRO2A-B
Krovna vent. jed., 4 vent. za DT/DTW, digit. term., RAL9005 RAL9005, Installation from inside of enclosure. Suitable for 800, 1000 and 1200mm deep enclosures. Not recommended for 600mm deep enclosures.	DTLTRO4D-B
Krovna vent. jed., 4 vent. za DT/DTW, analog. term., RAL9005 RAL9005, Installation from inside of enclosure	DTLTRO4A-B
Umetak s četkom za pod/krov, 70x316mm, za uvod kabela za DT 70x316mm, replaces two blind covers	DTZBRUSH02
Umetak s četkom za pod/krov, 70x500mm, za uvod kabela za DT 70x500mm, replaces three blind covers	DTZBRUSH03
Adapter zakretne ručke za polucilindar S-RACK s. ormara freestanding enclosure DT and wallmounting enclosure DTWI. For DTWI additionally necessary is DTZLOCK05	DTZLOCK02
Set za rednu ugradnju DT kom. ormara, D=800 i 1000mm, RAL9005 1 set = 2 pokrova (za vrh i dno) + 8x vijaka 6.3 x 12	DTRA0800-B
19" fiksna polica do 50kg, dubine 720mm, 1U, RAL9005 učvršćenje u 4 točke	DTFF1720-B
19" fiksna polica do 50kg, dubine 650mm, 2U, niskoprofilna učvršćenje u 4 točke, RAL9005	DTFL2650-B
19" vodilica kabela s 5 metalnih prstena, 1U, RAL9005	DTBC105R-B
19" vodilica kabela s 5 metalnih prstena 130mm, 1U, RAL9005	DTBC105RGB
19" set vijaka, kavezni matica+podložne pločice M6 (50 kom)	DTSRA050
LED rasvjeta za ormare, magnet, 230VAC, s kontaktom za vrata automatski u radu čim se otvore vrata, vanjsko napajanje	DTLIGHT01
19" set za uzemljenje za DT/DTW ormare, 1U, 10 priklj. točaka 4 x 4mm x 40cm žuto/zeleni vodič, s vijcima i maticama	DTRE0001
Prespojni panel 19", prazan, za 24 modula, 1U, crni, ECO crni, jezičac prespojnog kabela okrenut prema dolje	HSE0240SP
19" napojna letva s 9xshuko, alu 1U, kabel 3m, RAL7035	IU070114-3
19" napojna letva sa 7xshuko+prenaponska zaštita, 1.25U kabel s utikačem 2m, RAL7035	IU070113
19" napojna letva, 9xshuko+prekidač, kabel 2m, crna, alu, 1U ALU profil	Q7070114-A
19" Napojna letva, 7xshuko+prekidač, prenap.zaštita, crna 1U, kabel 2m, alu profil, crna	Q7070113-A
Preklopnik 24xRJ45 10/100/1000T, bez vent., unut. napajanje Metalno kućište, 19"	QLGSW2457