

Tehnički list za artikl: DTWI126060

# Zidni kom. ormar IP55 za unut. mont., š600 v663 d600, 19", 12U

RAL7035 svjetlo sivi, metalna vrata



## SCHRACK-Info

Network wallmount 19" IP55 Indoor Cabinets are designed for industrial applications. Based on EN60529 provides IP55 protection class against dust and water ingress.

The enclosure provides IP55 protection against dust and water.

After installation of fans or filters, IP54 is still met.

Application areas are semi-open areas like factories, warehouses, lean-to roof conditions, without no direct rain and environmental effects. Totally gasketed doors, IP55 performing swing handle locking with 3 point locking system and isolated cable entries provide best performance for water and dust ingress.

1,5 mm thick material monoblock welded construction, with epoxy polyester type powder coating which is RAL7035 Light Grey color, provides the corrosion resistance.

Passive ventilation via filtered inlets.

## TECHNICAL DATA


- Colour: RAL7035 Light Grey
- Front door opening angle is up to 140 degrees. Front door has an infused sealing gasket structure which provides excellent IP protection even under cold/hot weather conditions. The front door is grounded to the main body with yellow/green 4,0 mm diameter copper wire.
- Height: 12U
- Width: 600mm

- Depth: 600mm
- Maximum Load: 100kg
- Door: Glass door including keyed swing lock handle with 3point locking system provides security and anti-vandal structure, also maintaining the IP55 protection
- Included are 4 pcs. 3,0 mm thick wall mounts with matching washer and screws, as well as a cable entry flange with three glands: 2x PG21, 1 x PG48, 2 x PVC blind caps with 28mm diameter (installed in the floor) and a blind flange (accessory pack).
- Filters are included
- Cabinets are delivered with: 1 set = 2pcs 19" front rails. A second pair of 19" DTWIPROFxx rails for rear mounting is available as an option. This is required for 4-point mounting of heavy equipment.


## Tehnički podaci

|                                 |                          |
|---------------------------------|--------------------------|
| Neto širina (mm)                | 600,00                   |
| Neto visina (mm)                | 663,00                   |
| Neto dubina (mm)                | 600,00                   |
| Neto masa (kg)                  | 37,00                    |
| Min. temperatura okoline (°C)   | 5                        |
| Maks. temperatura okoline (°C)  | 40                       |
| Prikladno za širinu ormara (mm) | 600                      |
| Visina (mm)                     | 663                      |
| Boja                            | RAL 7035 (svijetlo siva) |
| Osnovna oznaka                  | Kućište                  |


## Mjerne skice: Zidni kom. ormar IP55 za unut. mont., š600 v663 d600, 19", 12U




Top view




Bottom view




Inside view




Front view




Side view




Rear view



Top inside view



Front door opening angle




3 point locking system

|       | A     |        | B      |        |
|-------|-------|--------|--------|--------|
|       | Min   | Max    | Min    | Max    |
| D=450 | 60 mm | 185 mm | 260 mm | 385 mm |
| D=600 | 60 mm | 335 mm | 260 mm | 535 mm |

|     | D      |
|-----|--------|
| 7U  | 298 mm |
| 9U  | 387 mm |
| 12U | 520 mm |
| 16U | 698 mm |
| 20U | 876 mm |

## Mjerne skice: Zidni kom. ormar IP55 za unut. mont., š600 v663 d600, 19", 12U



### Tablica artikla

| OPIS                                                           | KAT. BROJ  |
|----------------------------------------------------------------|------------|
| Zidni kom. ormar IP55 za unut. mont., š600 v663 d600, 19", 12U | DTWI126060 |
| RAL7035 svjetlo sivi, metalna vrata                            |            |
| <b>Dodatni pribor</b>                                          |            |
| Krovna vent. jedinica, 1xventilator za DTWI, s prekidačem      | DTLTR5521  |
| za zidne ormare IP55, svjetlosiva, instalacija izvan ormara    |            |

## Tablica artikla

| OPIS                                                                                                                                                               | KAT. BROJ  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <b>Dodatni pribor</b>                                                                                                                                              |            |
| Krovna vent. jedinica, 2xventilator za DTWI, s prekidačem<br>za zidne ormare IP55, svjetlosiva, instalacija izvan ormara                                           | DTLTR5522  |
| 19" profilni nosač set, 12U za S-RACK ormare DTWI<br>1 pak = 2 komada                                                                                              | DTWIPROF12 |
| Adapter zakretne ručke za polucilindar S-RACK s. ormara<br>freestanding enclosure DT and wallmounting enclosure DTWI. For DTWI additionally necessary is DTZLOCK05 | DTZLOCK02  |
| Komplet adaptera zakretne ručke za polucilindar za DTWI<br>potreban dodatni DTZLOCK02                                                                              | DTZLOCK05  |
| Preklopnik 24xRJ45 10/100/1000T, bez vent., unut. napajanje<br>Metalno kućište, 19"                                                                                | QLGSW2457  |
| 19" napojna letva sa 9xshuko, alu 1U, kabel 2m, RAL7035                                                                                                            | IU070114   |
| 19" napojna letva sa 7xshuko+prenaponska zaštita, 1.25U<br>kabel s utikačem 2m, RAL7035                                                                            | IU070113   |
| 19" napojna letva, 9xshuko+prekidač, kabel 2m, crna, alu, 1U<br>ALU profil                                                                                         | Q7070114-A |
| 19" Napojna letva, 7xshuko+prekidač, prenap.zaštita, crna<br>1U, kabel 2m, alu profil, crna                                                                        | Q7070113-A |