

Tehnički list za artikl: DV900330-A

# 19" svjetiljka s fluo cijevi, montaža na vijak ili magnet



## SCHRACK info

### Key-Features

- Lighting for Racks and Industry
- Compact-Lighting 26 mm wide
- Rotor with fastening units
- To fix with and always without tools
- Magnet is always used for fastening
- With fix mounted connection cable
- On metal, on profiles, into the 19" -rack
- Fastening by magnet, fastening by magnet and screw, fastening by magnet and snap in
- Screw on profiles have variable hole distance
- Worldwide usage: power supply unit 230V AC/50-60 Hz
- CE, ENEC, TÜV-GS
- With door switch connection (optional)

## Tehnički podaci

|                  |        |
|------------------|--------|
| Neto širina (mm) | 483,00 |
| Neto visina (mm) | 25,00  |
| Neto dubina (mm) | 55,00  |
| Neto masa (kg)   | 0,40   |

## Tehnički podaci - nastavak

|                                |     |
|--------------------------------|-----|
| Min. temperatura okoline (°C)  | -15 |
| Maks. temperatura okoline (°C) | 45  |

## Podatkovna tablica: 19" svjetiljka s fluo cijevi, montaža na vijak ili magnet

|                                   |                                                          |
|-----------------------------------|----------------------------------------------------------|
| <b>Elektrische Anschlusswerte</b> |                                                          |
| Nennleistung                      | 8W                                                       |
| Nennspannung                      | 230 V AC $\pm$ 10% bei 50-60 Hz                          |
| Nennstrom bei 230 V AC            |                                                          |
| Potentialfreier Kontakt           | über Steckverbinder, 2-poliger Kleingerätestecker, 2,5 A |
| Anschlussleitung                  | 2x0,75 mm <sup>2</sup> , 1,5m lang Mantelfarbe: schwarz  |
| <b>Schutzart/Schutzklasse</b>     |                                                          |
| Schutzart/Schutzklasse            | IP 20/11 (schutzzisoliert)                               |
| <b>Leuchtmittel</b>               |                                                          |
| Typ/Sockel                        | T5/G5                                                    |
| Lampenstart                       | Warmstart                                                |
| Mittlere Lebensdauer              | 10.000 h                                                 |
| Lichtfarbe                        | 4.300 K (kaltweiß)                                       |
| <b>Normen und Kennzeichnungen</b> |                                                          |
| Kennzeichnung                     | CE, ENEC                                                 |
| Prüfnormen                        | EN 60598EN 55015                                         |
| Störaussendungen                  | EN 61000-6-3                                             |
| Störfestigkeit                    | EN 61000-6-2                                             |
| Richtlinien                       | 73/23/EWG, 89/336/EWG, 2000/55/EG                        |
| Weitere Daten                     |                                                          |
| Betriebsgerät                     |                                                          |
|                                   |                                                          |
|                                   |                                                          |
|                                   |                                                          |
|                                   |                                                          |
|                                   |                                                          |

## Tablica artikla

| OPIS                                                         | KAT. BROJ  |
|--------------------------------------------------------------|------------|
| 19" svjetiljka s fluo cijevi, montaža na vijak ili magnet    | DV900330-A |
| <b>Dodatni pribor</b>                                        |            |
| Kabel za svjetiljku DV90033x-A za kontakt na vratima ormara  | DV900332   |
| Adapter za DS-, DSZ-, DSS- i mikroprekidač za vrata ASDSW010 | DSADA001   |
| Mikroprekidač za vrata IP65                                  | ACDSW010   |