

Tehnički list za artikl: ESL820984-

Rasvj. stup ALVA 940/ 170 OP 180° 600lm 840 MD IR DALI IP65

Diffuser: opal, graphite gray, protected from sea air, dirt-repellent thanks to powder coating with lotus effect, Integrated motion detector with DALI bus power supply, IR remote-controlled



Tehnički podaci

Neto visina (mm)	940,00
Neto promjer (mm)	170,00
Neto masa (kg)	7,83
Min. temperatura okoline (°C)	-25
Maks. temperatura okoline (°C)	40
Vrsta svjetiljke	Rasvjeta na stupu
Način montaže	Podna
Boja	grafit
Kut svjetlosti (°)	283
Radni napon AC (V)	200-240
Efikasnost sustava (lm/W)	37
Snaga (W)	17
Boja svjetla	Neutralno bijela
Temperatura boje (K)	4000
Faktor uzvrata boje	80
Stabilnot boje MacAdam (sdcm)	1

Tehnički podaci - nastavak

Svjetlosni tok (lm)	630
Životni vijek	70.000h (L80B50)
Dimabilno	DALI Da
Klasa zaštite	1
IP stupanj zaštite	IP65
Otpornost na udarce	IK09
Izvor svj. uklj.	Da
ØxV mm	170x940

Rasvj. stup ALVA 940/170 OP 180° 600lm 840 MD IR DALI IP65

Diffuser: opal, graphite gray, protected from sea air, dirt-repellent thanks to powder coating with lotus effect, Integrated motion detector with DALI bus power supply, IR remote-controlled

ESL820984