

Tehnički list za artikl: H6GTB07K5B

FlexBoot prespojni kabel, STP, cat.6a 10GB, plavi, 7.5m

4PPoE 100W, PREMIUM



Tehnički podaci

Kategorija	Cat.6A
Sastav kabela	4x2xAWG26/7
Kabelski oklop	S/FTP
Materijal vodiča	Stranded wire AWG 26/7 (0,457mm)
Konekcija	1:1
Brzina prijenosa	10Gbit
Broj parica	4
Oklop	Oklopljen
Vanjski omotač kabela	LSOH
LED funkcija	bez LED
Neto masa (kg)	0,27
Boja	plava
Min. temperatura okoline (°C)	-30
Maks. temperatura okoline (°C)	70
Radna temperatura (°C)	-25 to +60
Temperaturno područje - Instalacija (°C)	+0 to +50
Impedancija (Ohm)	100 ± 5

Tehnički podaci - nastavak

Otpor izolacije (MΩ*km)	≥ 2000MΩ/km
Kašnjenje uklopa (ns/m)	5 ≥ 10MHz: 4
RoHS	conform
Impedancija petlje (Ω/km)	300
4PPoE	Da
Duljina prespojnog kabela (m)	7,0

Tablica artikla

OPIS	NVP (%)	MASA BAKRA (kg/km)	KAT. BROJ
FlexBoot prespojni kabel, STP, cat.6a 10GB, plavi, 7.5m 4PPoE 100W, PREMIUM			H6GTB07K5B
Dodatni pribor			
S-JACK modul RJ45 oklopljen, Cat.6a 10GB, 4PPoE 100W SFB 24 kom. u kutiji			HSEMRJ6GS2
S-JACK modul RJ45 oklop., Cat.6a 10GB, 4PPoE 100W SFB .			HSEMRJ6GS1
TOOLLESS LINE modul RJ45 oklop., cat.6a 10GB, 4PPoE 100W SFB (SFB)			HSEMRJ6GBA
TOOLLESS LINE modul RJ45 oklop., cat.6a 10GB, 4PPoE 100W SFA .			HSEMRJ6GWA
S/FTP inst. kabel cat.7a, 4x2xAWG22/1, 1200MHz, LS0H-3, B2ca, 50% za rezanje	73	35	HSEKP422HB
S/FTP kabel cat.7a, 4x2xAWG22/1, 1500MHz, LS0H-3, Dca, plavi za rezanje	79	34	HSEKP422HP
S/FTP inst. kabel cat.7, 4x2xAWG23/1, 1000Mhz, LS0H-3, plavi za rezanje	79	25,5	HSEKP4233K
S/FTP inst. kabel cat.7, 4x2xAWG23/1, 1000MHz, LS0H, Dca, 40%, pl. za rezanje	78	28	HSEKP423HB
			HSEKF423HP
F/FTP inst. kabel cat.6a, 4x2xAWG23/1, 500MHz, LS0H-3, Dca, plavi za rezanje	80	20	HSEKP423GA
U/FTP kabel cat.6a, 4x2xAWG23/1, 500MHz, LS0H, Dca, plavi za rezanje	77	20	HSEKF423HB