


Tehnički list za artikl: H6GTN07K0N

Prespojni kabel RJ45 oklopljen cat.6a/ 10GB, LSOH, nar., 7m

4PPoE 100W, PREMIUM



SCHRACK-Info

Patchcords for generic, structured-network cabling systems RJ45/RJ45, 1:1 S/FTP double shielding. For transmission speeds up to 10 Gigabit Ethernet. Bandwidth up to 500 MHz. The cable offers maximum data security Pair in metal foil overall braid, as well as 360° shielded RJ45 connectors. This patchcord is suitable for use in offices and datacenters.

Standards:

- IEEE 802.3; 10BaseT; 100BaseT; 1000BaseT; 10GBaseT; IEEE 802.5 16MB; ISDN; ATM; Telefon
- Pin-Assignment: EIA/TIA 568B 1:1
- Cat. 6A, ISO/IEC 11 801 Ed.2.2 (2011-07) IEC 61935-2 Ed.3.0 (2010-07), EN 50173-1 and IEC 61156-6

Tehnički podaci

Kategorija	Cat.6A
Sastav kabela	4x2xAWG26/7
Kabelski oklop	S/FTP
Materijal vodiča	Stranded wire AWG 26/7 (0,457mm)
Konekcija	1:1
Brzina prijenosa	10Gbit
Broj parica	4

Tehnički podaci - nastavak

Oklop	Oklopljen
Vanjski omotač kabela	LS0H
LED funkcija	bez LED
Neto masa (kg)	0,23
Boja	narančasta
Min. temperatura okoline (°C)	-25
Maks. temperatura okoline (°C)	60
Radna temperatura (°C)	-25 do +60
Temperaturno područje - Instalacija (°C)	+0 to +50
Impedancija (Ohm)	100 ± 5
Otpor izolacije (MΩ*km)	≥ 2000MΩ/km
Kašnjenje uklopa (ns/m)	≥ 10MHz: 4,5
RoHS	conform
Impedancija petlje (Ω/km)	300
4PPoE	Da
Duljina prespojnog kabela (m)	7,0
Neto širina (mm)	270,00
Neto visina (mm)	235,00

Tablica artikla

OPIS	NVP (%)	MASA BAKRA (kg/km)	KAT. BROJ
Prespojni kabel RJ45 oklopljen cat.6a/10GB,LS0H,nar.,7m 4PPoE 100W, PREMIUM			H6GTN07K0N
Dodatni pribor			
S-JACK modul RJ45 oklopljen, Cat.6a 10GB, 4PPoE 100W SFB 24 kom. u kutiji			HSEMRJ6GS2
S-JACK modul RJ45 oklop., Cat.6a 10GB, 4PPoE 100W SFB .			HSEMRJ6GS1
TOOLLESS LINE modul RJ45 oklop., cat.6a 10GB, 4PPoE 100W SFB (SFB)			HSEMRJ6GBA
TOOLLESS LINE modul RJ45 oklop., cat.6a 10GB, 4PPoE 100W SFA (SFA)			HSEMRJ6GWA
S/FTP kabel cat.7a, 4x2xAWG22/1, 1500MHz, LS0H-3, Dca, plavi za rezanje	79	34	HSEKP422HP
S/FTP inst. kabel cat.7a,4x2xAWG23/1, 1200MHz,LS0H-3,Dca,pl. plavi, za rezanje	80	30	HSEKP422HK
S/FTP kabel cat.7,4x2xAWG23/1; 1.000MHz,LS0H;Dca,30%,plavi bubanj 500m	77	25	HSKP423PP5
F/FTP inst. kabel cat.6a,4x2xAWG23/1,500MHz,LS0H-3,Dca,plavi za rezanje	79	20	HSEKP423HA