

Tehnički list za artikl: H6GTW02K0W

# Prespojni kabel RJ45 STP cat.6a/ 10GB, LSOH, bijeli, 2.0m

4PPoE 100W, PREMIUM



## SCHRACK-Info

Patchcords for generic, structured-network cabling systems RJ45/RJ45, 1:1 S/FTP double shielding. For transmission speeds up to 10 Gigabit Ethernet. Bandwidth up to 500 MHz. The cable offers maximum data security Pair in metal foil overall braid, as well as 360° shielded RJ45 connectors. This patchcord is suitable for use in offices and datacenters.

### Standards:

- IEEE 802.3; 10BaseT; 100BaseT; 1000BaseT; 10GBaseT; IEEE 802.5 16MB; ISDN; ATM; Telefon
- Pin-Assignment: EIA/TIA 568B 1:1
- Cat. 6A, ISO/IEC 11 801 Ed.2.2 (2011-07) IEC 61935-2 Ed.3.0 (2010-07), EN 50173-1 and IEC 61156-6

## Tehnički podaci

|                  |                                  |
|------------------|----------------------------------|
| Kategorija       | Cat.6A                           |
| Sastav kabela    | 4x2xAWG26/7                      |
| Kabelski oklop   | S/FTP                            |
| Materijal vodiča | Stranded wire AWG 26/7 (0,457mm) |
| Konekcija        | 1:1                              |
| Brzina prijenosa | 10Gbit                           |
| Broj parica      | 4                                |

## Tehnički podaci - nastavak

| Oklop                                    | Oklopljen    |
|------------------------------------------|--------------|
| Vanjski omotač kabela                    | LS0H         |
| LED funkcija                             | bez LED      |
| Neto masa (kg)                           | 0,08         |
| Boja                                     | bijela       |
| Min. temperatura okoline (°C)            | -25          |
| Maks. temperatura okoline (°C)           | 60           |
| Radna temperatura (°C)                   | -25 do +60   |
| Temperaturno područje - Instalacija (°C) | +0 to +50    |
| Impedancija (Ohm)                        | 100 ± 5      |
| Otpor izolacije (MΩ*km)                  | ≥ 2000MΩ/km  |
| Kašnjenje uklopa (ns/m)                  | ≥ 10MHz: 4,5 |
| RoHS                                     | conform      |
| Impedancija petlje (Ω/km)                | 300          |
| 4PPoE                                    | Da           |
| Duljina prespojnog kabela (m)            | 2,0          |
| Neto širina (mm)                         | 240,00       |
| Neto visina (mm)                         | 200,00       |

## Tablica artikla

| OPIS                                                                                  | NVP (%) | MASA BAKRA (kg/km) | KAT. BROJ  |
|---------------------------------------------------------------------------------------|---------|--------------------|------------|
| Prespojni kabel RJ45 STP cat.6a/10GB, LS0H, bijeli, 2.0m<br>4PPoE 100W, PREMIUM       |         |                    | H6GTW02K0W |
| <b>Dodatni pribor</b>                                                                 |         |                    |            |
| S-JACK modul RJ45 oklopljen, Cat.6a 10GB, 4PPoE 100W SFB<br>24 kom. u kutiji          |         |                    | HSEMRJ6GS2 |
| S-JACK modul RJ45 oklop., Cat.6a 10GB, 4PPoE 100W SFB<br>.                            |         |                    | HSEMRJ6GS1 |
| TOOLLESS LINE modul RJ45 oklop., cat.6a 10GB, 4PPoE 100W SFB<br>(SFB)                 |         |                    | HSEMRJ6GBA |
| TOOLLESS LINE modul RJ45 oklop., cat.6a 10GB, 4PPoE 100W SFA<br>(SFA)                 |         |                    | HSEMRJ6GWA |
| S/FTP kabel cat.7a, 4x2xAWG22/1, 1500MHz, LS0H-3, Dca, plavi<br>za rezanje            | 79      | 34                 | HSEKP422HP |
| S/FTP inst. kabel cat.7a, 4x2xAWG23/1, 1200MHz, LS0H-3, Dca, pl.<br>plavi, za rezanje | 80      | 30                 | HSEKP422HK |
| S/FTP kabel cat.7, 4x2xAWG23/1; 1.000MHz, LS0H; Dca, 30%, plavi<br>bubanj 500m        | 77      | 25                 | HSKP423PP5 |
| F/FTP inst. kabel cat.6a, 4x2xAWG23/1, 500MHz, LS0H-3, Dca, plavi<br>za rezanje       | 79      | 20                 | HSEKP423HA |