

Tehnički list za artikl: HDCR100079

IS-1 serverski ormar s bočnim str.

600x2200x1200 RAL7035

lightgrey



SCHRACK-Info

Versatile application from small data rooms to large-scale data centres. Flexibly extendable for applications in cold or warm aisle enclosures. Equipped with passively vented doors (single or double wing), top cover for cable entry from above. The basic frame and all cladding parts have a high-quality, robust powder coating.

Frame clearance at front: 112mm**Static load capacity:** up to 18,000N**Material**

Basic frame: 1.50mm steel sheet

Doors: 1.50mm steel sheet

Side panels: 0.75mm steel sheet

482.6mm (19") mounting angles: 2.00mm steel sheet

Finish

Frame and cladding parts: powder-coated

Internal fittings: galvanized

Equipment

- 1 basic frame, demountable, with integrated 25-mm mounting hole pitch pattern on all sides
- 4 galvanised 482.6mm (19") mounting angles with square perforations at the front and sides for cage nuts in acc. with IEC 297 d EIA, incl. height unit pitch pattern and U-labelling (asymmetrical on the right for B 700 racks)
- 1 front door, passive venting (hexagonal perforations SW 6-6.7, free clearance 81%), with swing handle and profile half cylinder (30/10), EK333 lock and 4- point locking system
- 1 rear door, passive venting (hexagonal perforations SW 6-6.7, free clearance 81%), with swing handle and profile half cylinder (30/10), EK333 lock and 4- point locking system

- 2 side panels, screw-fastened, optional sash-fastener (only for cabinets with side panels, see table)
- 1 two-part top cover with knockouts at sides (not for width 600) and rear for cable entry and for up to 6 fans, rear cable entry knockout closed by brush strip
- Open base frame
- 4 levelling feet, incl. protective caps n 1 earthing set, mounted (all flat components earthed, central earthing point)

Inspections/Norms

Earthing in acc. with DIN VDE 0100-540

Components in acc. with IEC 297-1/2 (19")

Tehnički podaci

Neto širina (mm)	600,00
Neto visina (mm)	2.200,00
Neto dubina (mm)	1.200,00
Boja	RAL 7035 (svijetlo siva)
Visinska jedinica	47
Neto masa (kg)	135,00
Min. temperatura okoline (°C)	-10
Maks. temperatura okoline (°C)	60
IP stupanj zaštite	IP20
Razmak između razina (mm)	747

Mjerne skice: IS-1 serverski ormar s bočnim str. 600x2200x1200 RAL7035



Mjerne skice: IS-1 serverski ormar s bočnim str. 600x2200x1200 RAL7035



OPIS

KAT. BROJ

IS-1 serverski ormar s bočnim str. 600x2200x1200 RAL7035
lightgrey

HDCR100079