

Tehnički list za artikl: HSATS516EE

SAT multisklopka 5 ulaza 16 izlaza za Quattro + Quad LNB

uklj. napajanje 12V 1,6A



SCHRACK-Info

The multiswitch HSATS516EE Series 5 - with signal attenuation adjustment – is a device featuring integrated high-frequency components combined with proven mechanical design, offering a well-balanced product with an excellent price-to-performance ratio.

It deliberately omits unnecessary control elements, indicator lights, and buttons.

Thanks to the use of active modules, the series consistently delivers sufficient signal strength.

The multiswitch HSATS516EE Series 5 is compatible with both Quattro and Quad LNBs.

- DVBT2
- Power supply: 12V
- LNB Support: Quattro / Quad
- Ports: Gold-plated F connectors
- Quick Installation

Tehnički podaci

Neto duljina (mm)	253,00
Neto širina (mm)	128,00
Neto visina (mm)	54,00
Neto masa (kg)	0,75

Tehnički podaci - nastavak

Min. temperatura okoline (°C)	-20
Maks. temperatura okoline (°C)	50

Podatkovna tablica: SAT multisklopka 5 ulaza 16 izlaza za Quattro + Quad LNB

Artikelnummer		HSATS508EE	HSATS516EE
Numer Eingänge	SAT/IF	4 (F)	4 (F)
	Terr.	1 (F)	1 (F)
Ausgänge		8 (F)	16 (F)
terr. Verstärker 47 - 862MHz (Attenuator 0 dB... -15dB)		ja	ja
Auswahl LNB/Polarität		18V/22KHZ 13V/22KHZ 18V 13V	
Frequenzbereich	SAT/IF	950 - 2200MHz	950 - 2200MHz
	Terr.	47 - 862MHz	47 - 862MHz
Verlust über Teilnehmerausgänge (dB)	SAT/IF @ 950MHz	0dB	-1dB
	SAT/IF @ 2150MHz	8dB	7dB
	terr. Rec./Out 1-8	8dB	8dB
Alle Werte liegen innerhalb einer Toleranz von	+/- 1,5dB terr. Rec./Out 9-16		8dB
	terr. Rec./Out 17-24		
	terr. Rec./Out 24-32		

Tablica artikla

OPIS	KAT. BROJ
SAT multisklopka 5 ulaza 16 izlaza za Quattro + Quad LNB uklj. napajanje 12V 1,6A	HSATS516EE
Dodatni pribor	
SAT LNB Quattro za priključak na multisklopku, 40mm SBC42-70	HSATLSA--A
SAT završna utičnica R/TV/SAT, klasa A, RAL9010 uključen okvir 80x80mm i N/Ž kućište, RAL9010	HSATD3M
SAT utič. kraj. 4x,radio/CATV/2xSAT,kl.A,okvir 80x80,9010 uključen okvir 80x80mm i N/Ž kućište, RAL9010	HSATD4M
SAT ormarić čel., perf. ploča, zaključ.,400x400x200,RAL7035 RAL7035	HSATG442M
SAT ormarić čel., perf. ploča, zaključ.,600x600x200,RAL7035 RAL7035	HSATG662M
DIGI-SAT 3050 koaks.75Ohm 1.02/4.6/7.2, 105dB, LSOH, B2ca s1b, d1, a1 klasa A++, bijeli, trostruki oklop, bubanj 500m	XC1612023
DIGI-SAT 3040 koaks.75Ohm 1.02/4.6,110dB,kl.A,PVC,Eca,100m trostruki omotač, kolut 100m, mogućnost montaže na nosač XC1609809	XC1609801
DIGI-SAT 3010 koaks.75Ohm 1.13/6.8,95dB,kl.A,PVC,Eca,100m dvostruki omotač, kolut 100m	XC1609401
DIGI-SAT 3030 koaks.75Ohm 1.02/6.8,100dB,kl.A,PVC,Eca,100m Klasa A, bijeli, trostruki omotač, kolut 100m	XC1609901
DIGI-SAT 3010 koaks.75Ohm 1.13/6.8,95dB,kl.A,PVC,Eca,100m dvostruki omotač, kolut 100m	XC1609401
DIGI-SAT 3000 koaks.75Ω, 1.02/4.6 CCS,90dB,kl.A,PVC,Eca,100m Klasa A, bijeli, dvostruki omotač, kolut 100m	XC1608901
DIGI-SAT 3011 koaks.75Ohm 1.13/6.8,90dB,kl.A,PE,vanjski,100m dvostruki omotač, kolut 100m	XC1601501