

Tehnički list za artikl: HSELS04SCG

Optički prespojni panel 19", 1U, uklj. 4 spojnice SC SM

RAL7035, PREMIUM



Tehnički podaci

Neto širina (mm)	482,50
Neto visina (mm)	43,60
Neto dubina (mm)	211,50
Neto masa (kg)	2,70
Vlakno	singlemodno 9/125µm OS2
Boja	RAL 7035 (svijetlo siva)
Min. temperatura okoline (°C)	-10
Maks. temperatura okoline (°C)	70

Dimension drawing



Tablica artikla

OPIS	KAT. BROJ
Optički prespojni panel 19", 1U, uklj. 4 spojnice SC SM RAL7035, PREMIUM	HSELS04SCG
Dodatni pribor	
Optički prespojni kabel DX SC/UPC-SC/UPC,9/125µm OS2,LS0H žuti, 2.0m	HLP29CC02F
Optički prespojni kabel DX SC/UPC-SC/UPC,9/125µm OS2,LS0H žuti, 5.0m	HLP29CC05F
Optički prespojni kabel DX LC/UPC-SC/UPC,9/125µm OS2,LS0H žuti, 2.0m	HLP29LC02F
Optički prespojni kabel DX LC/UPC-SC/UPC,9/125µm OS2,LS0H žuti, 5.0m	HLP29LC05F
Optički prespojni kabel DX ST/UPC-SC/UPC,9/125µm OS2,LS0H žuti, 2.0m	HLP29TC02F
Optički prespojni kabel DX ST/UPC-SC/UPC,9/125µm OS2,LS0H žuti, 5.0m	HLP29TC05F
Optički prespojni kabel DX SC/UPC-FC/UPC,9/125µm OS2,LS0H žuti, 2.0m	HLP29CF02F
Optički prespojni kabel DX SC/UPC-FC/UPC,9/125µm OS2,LS0H žuti, 5.0m	HLP29CF05F