


Tehnički list za artikl: HSELS08SLG

Optički prespojni panel 19", 1U, uklj. 8 spojnica LC SM

RAL7035, PREMIUM



Tehnički podaci

Neto širina (mm)	482,50
Neto visina (mm)	43,60
Neto dubina (mm)	211,50
Neto masa (kg)	2,70
Vlakno	singlemodno 9/125µm OS2
Boja	RAL 7035 (svijetlo siva)
Min. temperatura okoline (°C)	-10
Maks. temperatura okoline (°C)	70

Dimension drawing



Tablica artikla

OPIS	KAT. BROJ
Optički prespojni panel 19", 1U, uklj. 8 spojnice LC SM RAL7035, PREMIUM	HSLS08SLG
Dodatni pribor	
Optički prespojni kabel DX LC/UPC-LC/UPC, 9/125µm OS2,LS0H žuti, 2.0m	HLP29LL02F
Optički prespojni kabel DX LC/UPC-LC/UPC, 9/125µm OS2,LS0H žuti, 5.0m	HLP29LL05F
Optički prespojni kabel DX LC/UPC-SC/UPC, 9/125µm OS2,LS0H žuti, 2.0m	HLP29LC02F
Optički prespojni kabel DX LC/UPC-SC/UPC, 9/125µm OS2,LS0H žuti, 5.0m	HLP29LC05F
Optički prespojni kabel DX LC/UPC-FC/UPC, 9/125µm OS2,LS0H žuti, 2.0m	HLP29LF02F