

Tehnički list za artikl: HSELS165CP

Opt. razdjelnik, 16 niti, SC, 50/ 125µm OM2, izvlačivi, 19", 1U

RAL7035, ECO



SCHRACK-Info

Chassis

- Two pieces removable 19" holders. Depth adjustable up to 40mm
- Sliding tray design:
for 12 SC Duplex couplers
- Blindcovers are used to cover unused openings
- Four openings for cable-gland
- Two fittings M22
- Material: Sheet steel, powder -coated, RAL 7035
- Sheet steel thickness:
Chassis: 1,0mm
Sliding tray: 1,25mm
Frontpanel: 1,4mm
19" holder: 1,5mm

SPLICE-CASSETTES

- For shrink splice protectors
up to 12 fibres: 1 splice-cassette
up to 24 fibers: 2 splice-cassettes

STANDARDS

- EN 50173-1, EN 61300-3-6, EN 61300-3-34

Tehnički podaci

Neto širina (mm)	480,00
Neto visina (mm)	44,00
Neto dubina (mm)	242,00
Neto masa (kg)	2,53
Boja	RAL 7035 (svijetlo siva)
Min. temperatura okoline (°C)	-10
Maks. temperatura okoline (°C)	70
Insercijski gubitak tipično (dB)	< 0,2
Prigušenje povratnog toka tipično (dB)	> 35
Vlakno	multimodno 50/125µm OM2
Broj vlakana	16

Tablica artikla

OPIS	KAT. BROJ
Opt. razdjelnik, 16 niti, SC, 50/125µm OM2, izvlačivi, 19", 1U RAL7035, ECO	HSELS165CP
Dodatni pribor	
Optička cjevčica za zaštitu spoja 60mm	HELSP00011
Optička cjevčica za zaštitu spoja 45mm	HELSP00010
Optički prespojni kabel duplex, SC/SC, 50/125µm OM2, 2.0m	HLP25CC02F
Optički prespojni kabel duplex, SC/SC, 50/125µm OM2, 5.0m	HLP25CC05F
Optički prespojni kabel duplex, LC/SC, 50/125µm OM2, 2.0m	HLP25LC02F
Optički prespojni kabel duplex, LC/SC, 50/125µm OM2, 5.0m	HLP25LC05F
Optički prespojni kabel duplex, ST/SC, 50/125µm OM2, 2.0m	HLP25TC02F
Optički prespojni kabel duplex, ST/SC, 50/125µm OM2, 5.0m	HLP25TC05F