


Tehnički list za artikl: HSELS169LG

Opt. razdjelnik, 16 niti, LC, 9/125µm OS2, 19", 1U, klase B

optički završeci umetnuti i pripremljeni za varenje, 19", 1U, RAL7035, klase B prema IEC 61753-1, PREMIUM



SCHRACK-Info

FO splice box extendable with quick release fastener and equipped with Grade B pigtails for splicing FO cables. The pull-out depth of 20 cm ensures easy access to the couplings. Furthermore the box can be set back by 40 mm. A possibility for the sloping input of section cables is integrated.

Properties Housing:

- 19", 1U installation, extendable
- incl. Depth adjustment
- front panel and side parts powder-coated
- colour: grey, RAL7035
- Lid metallic glossy
- Central screw bolt for fixing up to 4 splice cassettes
- Box can be tilted downwards when open

Standards:



50173-1, EN 61300-3-6, EN 61300-3-79

Tehnički podaci

Tehnički podaci - nastavak

Neto širina (mm)	482,50
Neto visina (mm)	43,60
Neto dubina (mm)	211,50
Neto masa (kg)	2,70
Vlakno	9/125 OS2 Singlemode / G.657.A1
Boja	RAL 7035 (svijetlo siva)
Min. temperatura okoline (°C)	-10
Maks. temperatura okoline (°C)	70
Broj vlakana	16
Spojnicica	LC

Dimension drawing



Tablica artikla

OPIS	KAT. BROJ
Opt. razdjelnik, 16 niti, LC, 9/125µm OS2, 19", 1U, klase B	HSELS169LG
optički završeci umetnuti i pripremljeni za varenje, 19", 1U, RAL7035, klase B prema IEC 61753-1, PREMIUM	
Dodatni pribor	
Optička cjevčica za zaštitu spoja 60mm	HELSP00011
Optička cjevčica za zaštitu spoja 45mm	HELSP00010
Alat za čišćenje optičkih utikača LC i MU	HSELSZT001
Pogodno za UPC i APC utikače. Više od 1000 ciklusa čišćenja.	

Tablica artikla

OPIS	KAT. BROJ
Dodatni pribor	
Mjerač snage s integriranim laserom (VFL) za optičke spojeve PAŽNJA: ovo je izvor svjetla Laser klase 2. Nikada ne gledajte u izvor. Uvijek koristite pokrov na VFL portu kad nije u uporabi. Preporučujemo uporabu specijalnih naočala za rad s laserskim izvorima svjetla.	HSELSZT003
Optički prespojni kabel DX LC/UPC-LC/UPC, 9/125µm OS2,LS0H žuti, 2.0m	HLP29LL02F
Optički prespojni kabel DX LC/UPC-LC/UPC, 9/125µm OS2,LS0H žuti, 5.0m	HLP29LL05F
Optički prespojni kabel DX LC/UPC-SC/UPC, 9/125µm OS2,LS0H žuti, 2.0m	HLP29LC02F
Optički prespojni kabel DX LC/UPC-SC/UPC, 9/125µm OS2,LS0H žuti, 5.0m	HLP29LC05F
Optički prespojni kabel DX LC/UPC-FC/UPC, 9/125µm OS2,LS0H žuti, 2.0m	HLP29LF02F