

Tehnički list za artikl: HSELS243TP

Opt. razdjelnik, 24 niti, ST, 50/125µm OM3, 19", 1U, klase C

optički završeci uključeni, 19", 1U, RAL7035, klase C prema IEC 61753-1, CLASSIC



SCHRACK-Info

Chassis

- Two pieces removable 19" holders. Depth adjustable up to 40mm
- Sliding tray design:
for 24 ST / FC couplers
- Blindcovers are used to cover unused openings
- Four openings for cable-gland
- Two fittings M22
- Material: Sheet steel, powder -coated, RAL 7035
- Sheet steel thickness:
Chassis: 1,0mm
Sliding tray: 1,25mm
Frontpanel: 1,4mm
19" holder: 1,5mm

SPLICE-CASSETTES

- For shrink splice protectors
up to 12 fibres: 1 splice-cassette
up to 24 fibers: 2 splice-cassettes

STANDARDS

- EN 50173-1, EN 61300-3-6, EN 61300-3-34

Tehnički podaci

Neto širina (mm)	480,00
Neto visina (mm)	44,00
Neto dubina (mm)	242,00
Neto masa (kg)	2,53
Vlakno	multimodno 50/125µm OM3
Boja	RAL 7035 (svijetlo siva)
Insercijski gubitak tipično (dB)	< 0,2
Prigušenje povratnog toka tipično (dB)	> 35
Min. temperatura okoline (°C)	-10
Maks. temperatura okoline (°C)	70
Broj vlakana	24

Tablica artikla

OPIS	KAT. BROJ
Opt. razdjelnik, 24 niti, ST, 50/125µm OM3, 19", 1U, klase C optički završeci uključeni, 19", 1U, RAL7035, klase C prema IEC 61753-1, CLASSIC	HSELS243TP
Dodatni pribor	
Optička cjevčica za zaštitu spoja 60mm	HELSP00011
Optička cjevčica za zaštitu spoja 45mm	HELSP00010
Alat za čišćenje optičkih utikača SC, ST, FC i E2000 Pogodno za UPC i APC utikače. Više od 1000 ciklusa čišćenja.	HSELSZT002
Mjerač snage s integriranim laserom (VFL) za optičke spojeve PAŽNJA: ovo je izvor svjetla Laser klase 2. Nikada ne gledajte u izvor. Uvijek koristite pokrov na VFL portu kad nije u uporabi. Preporučujemo uporabu specijalnih naočala za rad s laserskim izvorima svjetla.	HSELSZT003
Optički prespojni kabel DX ST/UPC-ST/UPC, 50/125µm OM3, LS0H tirkizni, 2.0m	HLP23TT02F
Optički prespojni kabel DX ST/UPC-ST/UPC, 50/125µm OM3, LS0H tirkizni, 5.0m	HLP23TT05F

Tablica artikla

OPIS	KAT. BROJ
Dodatni pribor	
Optički prespojni kabel DX ST/UPC-SC/UPC,50/125µm OM3,LS0H tirkizni, 2.0m	HLP23TC02F
Optički prespojni kabel DX ST/UPC-SC/UPC,50/125µm OM3,LS0H tirkizni, 5.0m	HLP23TC05F
Optički prespojni kabel DX LC/UPC-ST/UPC,50/125µm OM3,LS0H tirkizni, 2.0m	HLP23LT02F
Optički prespojni kabel DX LC/UPC-ST/UPC,50/125µm OM3,LS0H tirkizni, 5.0m	HLP23LT05F