



Tehnički list za artikl: HSELS249MP

Optički razdjelnik, 24xLC/APC, 9/125µm OS2, 19", 1U, klase C

optički završeci uključeni, 19", 1U, RAL7035, klase C prema IEC 61753-1, CLASSIC



Schrack-Info

Chassis

- Two pieces removable 19" holders. Depth adjustable up to 40mm
- Sliding tray design:
for 12 LC/APC Duplex couplers
- Blindcovers are used to cover unused openings
- Four openings for cable-gland

- Two fittings M22
- Material: Sheet steel, powder -coated, RAL 7035
- Sheet steel thickness:
 - Chassis: 1,0mm
 - Sliding tray: 1,25mm
 - Frontpanel: 1,4mm
 - 19" holder: 1,5mm

SPLICE-CASSETTES

- For shrink splice protectors
 - up to 12 fibres: 1 splice-cassette
 - up to 24 fibers: 2 splice-cassettes

STANDARDS

- EN 50173-1, EN 61300-3-6, EN 61300-3-34

Tehnički podaci

Neto širina (mm)	480,00
Neto visina (mm)	44,00
Neto dubina (mm)	242,00
Neto masa (kg)	2,53
Vlakno	9/125 OS2 Singlemode / G.652.D
Boja	RAL 7035 (svijetlo siva)
Insercijski gubitak tipično (dB)	< 0,2
Prigušenje povratnog toka tipično (dB)	> 50
Min. temperatura okoline (°C)	-10
Maks. temperatura okoline (°C)	70
Broj vlakana	24

Tablica artikla

OPIS	KAT. BROJ
Optički razdjelnik, 24xLC/APC,9/125µm OS2, 19", 1U, klase C	HSELS249MP
optički završeci uključeni, 19", 1U, RAL7035, klase C prema IEC 61753-1, CLASSIC	
Dodatni pribor	
Optička cjevčica za zaštitu spoja 60mm	HELSP00011
Optička cjevčica za zaštitu spoja 45mm	HELSP00010

Tablica artikla

OPIS	KAT. BROJ
Dodatni pribor	
Alat za čišćenje optičkih utikača LC i MU Pogodno za UPC i APC utikače. Više od 1000 ciklusa čišćenja.	HSELSZT001
Mjerač snage s integriranim laserom (VFL) za optičke spojeve PAŽNJA: ovo je izvor svjetla Laser klase 2. Nikada ne gledajte u izvor. Uvijek koristite pokrov na VFL portu kad nije u uporabi. Preporučujemo uporabu specijalnih naočala za rad s laserskim izvorima svjetla.	HSELSZT003
Optički pr. kabel DX LC-APC/LC-APC, 9/125µm OS2, LS0H, 1m žuti, 1.0m	HLP29MM01F
Optički pr. kabel DX LC-APC/SC-APC, 9/125µm OS2, LS0H, 1m žuti, 1.0m	HLP29MD01F
Optički pr. kabel DX LC-APC/LC-APC, 9/125µm OS2, LS0H, 2m žuti, 2.0m	HLP29MM02F
Optički pr. kabel DX LC-APC/SC-APC, 9/125µm OS2, LS0H, 2m žuti, 2.0m	HLP29MD02F
Optički pr. kabel DX LC-APC/LC-APC, 9/125µm OS2, LS0H, 3m žuti, 3.0m	HLP29MM03F
Optički pr. kabel DX LC-APC/SC-APC, 9/125µm OS2, LS0H, 3m žuti, 3.0m	HLP29MD03F
Optički pr. kabel DX LC-APC/LC-APC, 9/125µm OS2, LS0H, 5m žuti, 5.0m	HLP29MM05F
Optički pr. kabel DX LC-APC/SC-APC, 9/125µm OS2, LS0H, 5m žuti, 5.0m	HLP29MD05F
Optički pr. kabel DX LC-APC/LC-APC, 9/125µm OS2, LS0H, 10m žuti, 10.0m	HLP29MM10F
Optički pr. kabel DX LC-APC/SC-APC, 9/125µm OS2, LS0H, 10m žuti, 10.0m	HLP29MD10F