


Tehnički list za artikl: HSELS24SLP

# Opt. razdjelnik, 24 niti, LC, 50/125µm OM5, izvlačivi, 19", 1U

prema IEC 61753-1, RAL7035, uključeni optički završeci, CLASSIC



## Schrack-Info

These spliceboxes are delivered assembled with already installed couplers and enclosed pigtails (all connectors come with ceramic ferrule).

The spliceboxes are depth-adjustable using the two 19" brackets.

The spliceboxes have one, two or four splice trays depending on the number of fibres with integral splice organisers for shrink-on splice protectors and is designed for up to 4 cable entries, equipped with one M20 cable entry by default.

Blind covers are used to close off unused cable entry ports.

Two versions for up to 48 fibres in a sliding tray design are available:

- with 24 LC-Duplex couplers
- with 24 SC-Duplex couplers
- Material: zinc-coated steel
- Installation: 19", 1U
- Dimensions W x H x D: 483 x 44 x 240mm
- Housing color: RAL7035 Light grey
- Color of couplers (LC and SC): Lime-green
- Dustcovers (LC and SC): Included

## Tehnički podaci

|                  |        |
|------------------|--------|
| Neto širina (mm) | 480,00 |
|------------------|--------|

## Tehnički podaci - nastavak

|                                        |                          |
|----------------------------------------|--------------------------|
| Neto visina (mm)                       | 44,00                    |
| Neto dubina (mm)                       | 242,00                   |
| Neto masa (kg)                         | 2,53                     |
| Vlakno                                 | 50/125 OM5 Multimode     |
| Boja                                   | RAL 7035 (svijetlo siva) |
| Insercijski gubitak tipično (dB)       | < 0,2                    |
| Prigušenje povratnog toka tipično (dB) | > 35                     |
| Min. temperatura okoline (°C)          | -10                      |
| Maks. temperatura okoline (°C)         | 70                       |
| Broj vlakana                           | 24                       |

## Tablica artikla

| OPIS                                                                                                                                                                                                                                                                               | KAT. BROJ  |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| Opt. razdjelnik, 24 niti, LC, 50/125µm OM5, izvlačivi, 19", 1U<br>prema IEC 61753-1, RAL7035, uključeni optički završeci, CLASSIC                                                                                                                                                  | HELS24SLP  |
| <b>Dodatni pribor</b>                                                                                                                                                                                                                                                              |            |
| Optička cjevčica za zaštitu spoja 60mm                                                                                                                                                                                                                                             | HELSP00011 |
| Optička cjevčica za zaštitu spoja 45mm                                                                                                                                                                                                                                             | HELSP00010 |
| Alat za čišćenje optičkih utikača LC i MU<br>Pogodno za UPC i APC utikače. Više od 1000 ciklusa čišćenja.                                                                                                                                                                          | HELSZT001  |
| Mjerač snage s integriranim laserom (VFL) za optičke spojeve<br>PAŽNJA: ovo je izvor svjetla Laser klase 2. Nikada ne gledajte u izvor. Uvijek koristite pokrov na VFL portu kad nije u uporabi.<br>Preporučujemo uporabu specijalnih naočala za rad s laserskim izvorima svjetla. | HELSZT003  |
| Optički prespojni kabel DX LC/UPC-LC/UPC, 50/125µm OM5, LS0H<br>limeta zeleni, 0.5m                                                                                                                                                                                                | HLP2SLL00F |
| Optički prespojni kabel DX LC/UPC-LC/UPC, 50/125µm OM5, LS0H<br>limeta zeleni, 2.0m                                                                                                                                                                                                | HLP2SLL02F |
| Optički prespojni kabel DX LC/UPC-LC/UPC, 50/125µm OM5, LS0H<br>limeta zeleni, 5.0m                                                                                                                                                                                                | HLP2SLL05F |