

Tehnički list za artikl: IL036239-F

Nazidni okvir s vratima za Modul 2000 | 2A-39 | dubina 300mm

čelični lim, RAL7035, 1 prirubnica gore + 1 prirubnica dolje



SCHRACK info

- Modularna izvedba, uzidni okvir s vratima
- Materijal: praškasto lakirani čelični lim debljine 1.25mm
- praškasto lakirani ormar ispitivan i certificiran u skladu s EN 62208:2011 i EN 60529:1991, klasa zaštite I prikladna za TT/TN i IT mreže, zaštićen izolacija u skladu s ÖVE-IM 12
- The enclosures with 300mm and 400mm depth are designed with riveted steel sheet back panel and 3-point rod lock with swing handle prepared for installation of various half cylinder locks
- Nazivni napon U_e : 230/400V/50Hz
- Nazivni napon izolacije U_i : 1000V
- Nazivni udarni podnosivi napon U_{imp} : 6kV
- Nazivna kratkotrajno podnosiva struja I_{cw} : 25kA / 1s
- Nazivna podnosiva vršna struja kratkog spoja I_{pk} : 54kA
- nazivna uvjetna struja kratkog spoja I_{cc} : 25kA
- Priključak zaštitnog uzemljenja: zavareni vijak M6, $I^2t=3,6 \times 10^6 \text{ A}^2\text{s}$
- Klasa zaštite: I
- Temperatura okoline: -5 do +40°C
- Relativna vlažnost zraka: 50% pri +40°C
- Maks. dozvoljeno opterećenje: 150kg za samostojeće / 80kg kod montaže na zid (bez dodatnih potpora) / vrata 10kg
- EMC: EMC okolina 1


- Umetak razdjelnika, širina D: 500mm / Visina E: 1795mm



Tehnički podaci


Neto širina (mm)	590,00
Neto visina (mm)	1.885,00
Neto dubina (mm)	300,00
Neto masa (kg)	15,00
EAN	9004840254570
Disipacija snage (W)	-543,00
Tip	Nazidni
Boja	RAL 7035
Širina brojila	2
Visinska jedinica	39
IP stupanj zaštite	IP20C
Osnovna oznaka	Okvir

Mjerne skice: Nazidni okvir s vratima za Modul 2000 | 2A-39 | dubina 300mm




Mjerne skice: Nazidni okvir s vratima za Modul 2000 | 2A-39 | dubina 300mm


IL900102



IL900105



IL900415-F



[mm]

Podatkovna tablica: Nazidni okvir s vratima za Modul 2000 | 2A-39 | dubina 300mm

Type	Article number	Number of gland plates above	Number of gland plates below	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	Radiant power loss [W]*
Depth 100 mm									
2A12	IL006912-F	-	-	640	590	100	500	555	-140
2A18	IL006918-F	-	-	915	590	100	500	830	-193
Depth 180 mm									
1A7	IL006107-F	-	-	410	380	180	290	325	-86
1A12	IL006112-F	-	-	640	380	180	290	555	-124
2A7	IL006207-F	-	-	410	590	180	500	325	-119
2A12	IL006212-F	-	-	640	590	180	500	555	-170
2A12	IL0062121F	1	-	640	590	180	500	555	-170
2A12	IL0062122F	1	1	640	590	180	500	555	-170
3A12	IL006312-F	-	-	640	810	180	720	555	-221
4A12	IL006412-F	-	-	640	1030	180	940	555	-273
Depth 250 mm									
1A16	IL006116-F	-	-	830	380	250	290	745	-183
1A18	IL006118-F	-	-	915	380	250	290	830	-199
1A21	IL006121-F	-	-	1055	380	250	290	970	-225
1A24	IL006124-F	-	-	1195	380	250	290	1105	-252
1A28	IL006128-F	-	-	1380	380	250	290	1290	-286
1A42	IL006142-F	-	-	2025	380	250	290	1935	-408
2A18	IL006218-F	-	-	915	590	250	500	830	-264
2A18	IL0062181F	1	-	915	590	250	500	830	-264
2A18	IL0062182F	1	1	915	590	250	500	830	-264
2A21	IL006221-F	1	-	1055	590	250	500	970	-299
2A24	IL006224-F	1	-	1195	590	250	500	1105	-333
2A28	IL006228-F	1	-	1380	590	250	500	1290	-379
2A33	IL006233-F	1	-	1605	590	250	500	1520	-434
2A39	IL006239-F	1	1	1885	590	250	500	1795	-503
2A42	IL006242-F	1	1	2025	590	250	500	1935	-537
2A45	IL006245-F	1	1	2160	590	250	500	2070	-570
3A18	IL006318-F	-	-	915	810	250	720	830	-334
3A21	IL006321-F	1	-	1055	810	250	720	970	-376
3A24	IL006324-F	1	-	1195	810	250	720	1105	-419
3A28	IL006328-F	1	-	1380	810	250	720	1290	-475
3A33	IL006333-F	1	-	1605	810	250	720	1520	-544
3A39	IL006339-F	1	1	1885	810	250	720	1795	-629
3A42	IL006342-F	1	1	2025	810	250	720	1935	-672
3A45	IL006345-F	1	1	2160	810	250	720	2070	-713
4A18	IL006418-F	-	-	915	1030	250	940	830	-403
4A21	IL006421-F	2	-	1055	1030	250	940	970	-454
4A24	IL006424-F	2	-	1195	1030	250	940	1105	-505
4A28	IL006428-F	2	-	1380	1030	250	940	1290	-572
4A33	IL006433-F	2	-	1605	1030	250	940	1520	-654
4A39	IL006439-F	2	2	1885	1030	250	940	1795	-756
4A42	IL006442-F	2	2	2025	1030	250	940	1935	-807
4A45	IL006445-F	2	2	2160	1030	250	940	2070	-856
5A24	IL006524-F	2	-	1195	1230	250	1140	1105	-583
5A28	IL006528-F	2	-	1380	1230	250	1140	1290	-660
5A33	IL006533-F	2	-	1605	1230	250	1140	1520	-754
5A39	IL006539-F	2	2	1885	1230	250	1140	1795	-871
5A42	IL006542-F	2	2	2025	1230	250	1140	1935	-930

5A45	IL006545-F	2	2	2160	1230	250	1140	2070	-986
Depth 300 mm									
2A39	IL036239-F	1	1	1885	590	300	500	1795	-543
2A42	IL036242-F	1	1	2025	590	300	500	1935	-580
2A45	IL036245-F	1	1	2160	590	300	500	2070	-616
3A39	IL036339-F	1	1	1885	810	300	720	1795	-673
3A42	IL036342-F	1	1	2025	810	300	720	1935	-718
3A45	IL036345-F	1	1	2160	810	300	720	2070	-762
4A39	IL036439-F	2	2	1885	1030	300	940	1795	-802
4A42	IL036442-F	2	2	2025	1030	300	940	1935	-856
4A45	IL036445-F	2	2	2160	1030	300	940	2070	-907
5A39	IL036539-F	2	2	1885	1230	300	1140	1795	-920
5A42	IL036542-F	2	2	2025	1230	300	1140	1935	-981
5A45	IL036545-F	2	2	2160	1230	300	1140	2070	-1040
Depth 400 mm									
2A42	IL009242-F	1	1	2025	590	400	500	1935	-666
3A42	IL009342-F	1	1	2025	810	400	720	1935	-810
4A42	IL009442-F	2	2	2025	1030	400	940	1935	-954
5A42	IL009542-F	2	2	2025	1230	400	1140	1935	-1085

* Max. radiated power of housing calculated as a wall-mounted single fixed with $\Delta T = 35K$.

Detailed information and legal notes see page 9

Tablica artikla

OPIS	KAT. BROJ
Nazidni okvir s vratima za Modul 2000 2A-39 dubina 300mm čelični lim, RAL7035, 1 prirubnica gore + 1 prirubnica dolje	IL036239-F
Dodatni pribor	
Ploča za uvod kabela, 18 rupa 18-30mm, gumene uvodnice 440x130x33mm (ŠxVxD), za ormare IL001/006/009/036 širine 2, 3, 4, 5. Kabelski prolazi: 18x (18-30)mm	IL900105
Ploča za uvod kabela, 48 rupa 13-30mm, gumene uvodnice 426x130x15mm (ŠxVxD), za ormare IL001/006/009/036 širine 2,3, 4, 5. Kabelski prolazi: 28x13mm, 16x17mm i 4x30mm	IL900102
Postolje za nazidne ormare dubine 300mm, bočni dijelovi visina 100mm, isporuka u paru (lijevi + desni bočni dio), mogućnost sastavljanja 2 postolja u postolje visine 200mm, primjenjivi kod IL091130 ormara u izvedbi IP20-C i IP54	
Postolje za nazidne razdj. M2000, prednji dio, 2PB, U-profil redizajnirani U-profil dubine 8 mm, 2 mm čelični lim	IL091200-S
Bočni panel podnožja 300mm, visina=100mm, 1 par s otvorom za uvod kabela 190x50mm, ventilirano, vijci sadržani u isporuci	IL090130-V
Bočni panel podnožja 300mm, visina=200mm, 1 par s otvorom za uvod kabela 190x50mm, ventilirano, vijci sadržani u isporuci	IL090230-V