

Tehnički list za artikl: IL190125-T

# Transducer Tyrol 125A indoor with pedestal, 1 in/out

IP20C, Protection class I, sheet steel, RAL7035 (Light grey), H=2025 W=810 D=300mm



## Tehnički podaci

|                      |                           |
|----------------------|---------------------------|
| Neto širina (mm)     | 810,00                    |
| Neto visina (mm)     | 2.025,00                  |
| Neto dubina (mm)     | 300,00                    |
| Neto masa (kg)       | 150,00                    |
| EAN                  | 9004840883923             |
| Disipacija snage (W) | -718,00                   |
| Austrijske pokrajine | Tirol                     |
| IP stupanj zaštite   | IP20C                     |
| Nazivna struja (A)   | 125                       |
| Klasa zaštite        | I                         |
| Otpornost na udarce  | IK08                      |
| Boja                 | RAL 7035 (svijetlo siva)  |
| Tip                  | Transducer                |
| Mjesta za brojila    | 3                         |
| Materijal            | Powder-coated Sheet Steel |
| Širina (mm)          | 810                       |
| Visina (mm)          | 2025                      |

## Tehnički podaci - nastavak

|                   |           |
|-------------------|-----------|
| Dubina (mm)       | 300       |
| Basic Description | Enclosure |

## Tablica artikla

| OPIS                                                                               | KAT. BROJ  |
|------------------------------------------------------------------------------------|------------|
| Transducer Tyrol 125A indoor with pedestal, 1 in/out                               | IL190125-T |
| IP20C, Protection class I, sheet steel, RAL7035 (Light grey), H=2025 W=810 D=300mm |            |
| <b>Dodatni pribor</b>                                                              |            |
| Polucilindar brava H36000 1006-2U s 3 ključa                                       | IL900381   |