

Tehnički list za artikl: INSR2432--

Grebenasta sklopka (glavna), 0-1/4P/ 32A, montaža na DIN nosač

Izvedba/tip Emergency sklopka, Nazivna struja 32A, Polovi 4, IP stupanj zaštite IP40 (front), IP20 (terminals), Neutral conductor contacts Neutral conductor early-make, late-break design (closes before and opens after the phase conductors to prevent voltage displacement)



Tehnički podaci

Izvedba/tip	Emergency sklopka
Nazivna struja (A)	32
Polovi	4
Način montaže	DIN nosač
Norma	IEC 60947, EN 60947, VDE 0660
Nazivni napon izolacije [Ui] (V)	690
Nazivni udarni podnosivi napon [Uimp] (V)	6000
Nazivna kratkotrajno podnosiva struja Icw	500
Nazivna struja kratkog spoja	10kA @ 440V / 6kA @ 690V
Kratkospojna zaštita, maks. rastalni osigurač	50
Frekvencija (Hz)	50/60

Tehnički podaci - nastavak

Operating Current	AC-22A - 690V - 32A AC-23A - 690V - 13A AC-23A - 230V - 22A AC-23A - 400V - 22A AC-3 - 400V - 20A AC-3 - 690V - 11.5A AC-3 - 230V - 20A AC-21A - 690V - 32A
Switching Capacity	AC-23A - 690V - 11.5kW AC-3 - 230V - 5.5kW AC-3 - 400V - 9.5kW AC-23A - 230V - 6kW AC-3 - 690V - 9.5kW AC-23A - 400V - 11.5kW
According to UL 508 / CSA	
Tip priključka	UL/CSA - AWG 14-6
Radni napon AC (V)	600
Thermal rated continuous current (A)	32
Active Power	3x600VAC - 22Hp 1x240VAC - 3Hp 3x480VAC - 20Hp 1x120VAC - 2Hp 3x240VAC - 10Hp 3x120VAC - 3Hp
Priključak	
Konvencionalna termička struja Ith (A)	32
Moment pritezanja (Nm)	3
Presjek priključnih vodiča, višezilni kabel (mm²)	2,5-16
Presjek priključnih vodiča, Jednožični (mm²)	2,5-16
Presjek priključnih vodiča, finožični kabel s tuljkom (mm²)	2,5-16
Retrofit contacts	
Pomoćni kontakti	Maximum 2x INSHK001 -- permitted. 1x INSHK001 -- can be snapped on to the left side of the main contact and 1x INSHK001 -- to the right side of the main contact. Maximum configuration 2x NC contact / 2x NO contact. The switching behavior is the same regardless of whether the auxiliary contact is snapped on to the left or right side of the main contact.
Neutral conductor contacts	Neutral conductor early-make, late-break design (closes before and opens after the phase conductors to prevent voltage displacement)
Radna temperatura	-25°C to +55°C
Mehanički životni vijek	100000 switching cycles
Gubitak snage po polu (W)	1,50
Zaštita od dodira	finger-proof and back-of-hand-proof according to VDE 0106 Part 100
IP stupanj zaštite	IP40 (front), IP20 (terminals)




Tehnički podaci - nastavak

Lockable	With 2 locks, each with a shackle lock diameter of 4-6 mm
Neto duljina (mm)	81,00
Neto širina (mm)	49,00
Neto visina (mm)	45,00
Min. temperatura okoline (°C)	-25
Maks. temperatura okoline (°C)	55

Schaltbild INSR2432--



Maßbild INSR2432--



Montageanleitung INSHK Hilfskontakte

Hilfskontakt
Auxiliary contact
INSHK001--



Montageanleitung INSR Hutschienenmontage Schalter



Tablica artikla

OPIS	KAT. BROJ
Grebenasta sklopka (glavna), 0-1/4P/32A, montaža na DIN nosač Izvedba/tip Emergency sklopka, Nazivna struja 32A, Polovi 4, IP stupanj zaštite IP40 (front), IP20 (terminals), Neutral conductor contacts Neutral conductor early-make, late-break design (closes before and opens after the phase conductors to prevent voltage displacement)	INSR2432
Dodatni pribor	
Pomoćni kontakt 1 N/O+1 N/C za INSR, INSP i INSA grebenaste za INSR, INSP i INSA Grebenaste sklopke	INSHK001