

Tehnički list za artikl: KC188041--

Samostojeći ormar, 1-vrata, IP55, 1800x800x400mm (VxŠxD)

čelični lim, RAL7035, bez montažne ploče, zaključavanje u četiri točke sa zakretnom ručicom



SCHRACK-Info

- **Material** : Corpus: 1.5 mm galvanised sheet steel. Doors: Single door and double door: 2 mm sheet steel
- **Mounting plate** : 3 mm galvanised sheet steel. Double folded, mounted in the enclosure, fully adjustable in depth in 25 mm increments with depth adjustment brackets ACMPD002. As insertion aid of the mounting plate we recommend the use of slide-in rails ACCLT300 (for depth 300 mm), ACCLT400 (for depth 400 mm) and ACCLT500 (for depth 500 mm). The slide-in rails are inserted in the floor, after sliding and fixing of the mounting plate they can be removed and reused in the next enclosure
- **Bottom plates** : 1 mm galvanised sheet steel, divided in two parts
- **Frame** : Folded and seam welded reversed open profile with 25 mm hole pattern according to DIN 43660. Including inside circumferential hole pattern
- **Door** : On single door enclosures, the door is mounted on four double-sided hinges allowing left- or right-hand opening. On double door enclosures, hinges are not reversible. Doors for left-hand opening have to be ordered separately. All door panels include the door mounting frame with 25 mm hole pattern. The left Z-wing is locked separately with an inner three-point lock
- **Lock** : Four-point rod lock with push-pull handle with spring adjustment and 5 mm DIN double-bit key lock (DDB), does not slide inward. The standard lock can be exchanged for profile half cylinder (DIN cylinder) and other inserts from the range of accessories. Double doors are designed with a left-side inner pivot lever
- **Rear panel** : Mounted with M6 torx screws. Replacement against additional door from the back side is possible. For 1600 mm wide enclosures the rear panel is divided
- **Roof panel** : Removable
- **Earthing** : All panels are earthed through their fittings and are equipped with a separate earthing stud

- **Degree of protection** : Single door and double door IP55
- **Impact resistance** : IK10
- **Finish** : Textured powder coating
- **Color** : RAL7035 (Light grey)
- **Delivery includes** : Enclosure with door, rear panel, roof panel, bottom plates, mounting plate with fixing material for the nearest position of the rear panel and earthing studs. Delivered on a pallet with equal width as the enclosure.



Tehnički podaci

Neto širina (mm)	800,00
Neto visina (mm)	1.800,00
Neto dubina (mm)	400,00
Neto masa (kg)	99,20
Min. temperatura okoline (°C)	-10
Maks. temperatura okoline (°C)	60
IP stupanj zaštite	IP55
Klasa zaštite	I
Materijal	Čelični lim
Boja	RAL 7035 (svijetlo siva)
Širina (mm)	800
Visina (mm)	1800
Dubina (mm)	400
Debljina stijenke tijela (mm)	1,50
Montažna ploča	Bez montažne ploče
Debljina stijenke vrata (mm)	2
Broj dijelova donje ploče	2
Opteretivost vrata (kg)	100
Broj vrata	1
Širina podne ploče (mm)	630
Tip	Kompaktni samostojeći ormar
Maksimalna opteretivost (kg)	700
Opteretivost montažne ploče (kg)	700
Disipacija snage (W)	-724,00

Tablica artikla

OPIS	KAT. BROJ
Samostojeći ormar, 1-vrata, IP55, 1800x800x400mm (VxŠxD) čelični lim, RAL7035, bez montažne ploče, zaključavanje u četiri točke sa zakretnom ručicom	KC188041
Dodatni pribor	
LED ligh for EC, infra (not available in this country)	IU006519CZ
Montažna ploča za AC ormare 1800x800mm (VxŠ)	ACMP1808
Podnožje prema dubini AC ormara 400x100mm, RAL9005 Isporuka sadrži lijevi i desni element (par, prema dubini ormara) te 4 (predmontirana) kutna elementa	ACSOT041
Podnožje prema širini AC ormara 800x100mm, RAL9005 Isporuka sadrži prednji i stražnji element podnožja (par, prema širini ormara)	ACSOB081
Podnožje prema dubini AC ormara 400x200mm, RAL9005 Isporuka sadrži lijevi i desni element (par, prema dubini ormara) te 4 (predmontirana) kutna elementa	ACSOT042
Podnožje prema širini AC ormara 800x100mm, RAL9005 Isporuka sadrži prednji i stražnji element podnožja (par, prema širini ormara)	ACSOB081
Krovna ploča 800x400, s otvorima za prirubnice Priladno za AC/KC ormare, pripremljeni s otvorima za prirubnice za montažu prirubnica za prolaz kabela, odgovarajuće prirubnice: WSTBT2117G, WSTBT2125G, WSTBT2130G, WSTBT2135G, WSTBT2150G, IG712100, IG712102, IG712200, IG712205, IG712211, IG712222, IG712223, IG712512, IG712516	ACRCE0804
Klizna šina za ugradnju mont. pl. u AC/KC ormar dubine 400mm Praktičan pribor za umetanje montažne ploče u ormar. Nakon umetanja i fiksiranja montažne ploče šine se uklanjaju te se u istu svrhu mogu koristiti kod sljedećeg ormara. Materijal: čelični lim debljine 2mm. Pakiranje: 1 par.	ACCLT400
Transportne ušice M12 za AC, KC, AT, KT ormare, 4 komada za podizanje kompaktnog samostojećeg ili jednog serijskog ormara	ACLE9301
Spremnik za dokumentaciju, samoljepljivi, A4	ASDRA400
Zakretna ručica bez umetka, crna, feder opruga without insert	ACLSC502
Adapter za polucilindar bravu za zakretnu ručicu, za ormare AC/KC	ASLS2100
Adapter za umetak brave sa tipkom za ormare AC/KC	ASLSS1537
Kavezne matice M6 (pakiranje 10 komada)	ACCNM615
Vijak za maticu M6x16 prema ISO 7380 (pak.=10 kom.) PU=10 pieces	ACCNK006
Kavezne matice M8 (pakiranje 10 komada)	ACCNM815
Vijak za maticu M8x16 prema ISO 7380 PAK=10 komada	ACCNK008
Ključ za 5mm "double-bit" bravu 1 komad u isporuci	DV903532