

Tehnički list za artikl: LI1000388-

ANINDA LED 16W, 3000K, 1040lm, L-605mm 700mA, srebrne b.

bez drivera, zidna i stropna ugradna svjetiljka



Tehnički podaci

Neto duljina (mm)	605,00
Neto širina (mm)	58,00
Neto visina (mm)	86,00
Neto masa (kg)	1,05
Otvor (mm)	590x45
Način montaže	Stropna ugradna Zidna ugradna
Boja	srebrna
Materijal	Aluminij Acrylic
Proizvođač	03-SLV
Operation current mA (mA)	700
Snaga (W)	16
System efficiency (lm/W)	65
Temperatura boje (K)	3000
Faktor uzvrata boje	80
Svjetlosni tok (lm)	1040

Tehnički podaci - nastavak

Klasa zaštite	III
Energetska klasa	A++ A+ A
Ugradna dubina (mm)	85
Izvor svj. uklj.	Da
(DxŠxV) mm	605x58x86
OTVOR mm	590x45

Tablica artikla

OPIS	KAT. BROJ
ANINDA LED 16W, 3000K, 1040lm, L-605mm 700mA, srebrne b. bez drivera, zidna i stropna ugradna svjetiljka	LI1000388
Dodatni pribor	
LED driver, 700mA, 12.5-25W, dimabilan	LI1001133
LED driver, 700mA, 12.6-19.6W, dimabilan	LI1001136
TCI LED-Driver 50VA, 350-1050mA Dip-Switch, DALI- dim. inkl. Cable relief	LI464032