

Tehnički list za artikl: LI1000389-

ANINDA LED 16W, 3000K, 2230lm, L-1205mm 700mA, crne mat b.

bez drivera, zidna i stropna ugradna svjetiljka



Tehnički podaci

Neto duljina (mm)	1.205,00
Neto širina (mm)	58,00
Neto visina (mm)	86,00
Neto masa (kg)	1,95
Otvor (mm)	1190x45
Način montaže	Stropna ugradna Zidna ugradna
Boja	crna mat
Materijal	Aluminij Acrylic
Proizvođač	03-SLV
Operation current mA (mA)	700
Snaga (W)	16
System efficiency (lm/W)	139
Temperatura boje (K)	3000
Faktor uzvrata boje	80
Svjetlosni tok (lm)	2230

Tehnički podaci - nastavak

Klasa zaštite	III
Energetska klasa	A++ A+ A
Ugradna dubina (mm)	85
Izvor svj. uklj.	Da
(DxŠxV) mm	1205x58x86
OTVOR mm	1190x45

Tablica artikla

OPIS	KAT. BROJ
ANINDA LED 16W, 3000K, 2230lm, L-1205mm 700mA, crne mat b. bez drivera, zidna i stropna ugradna svjetiljka	LI1000389
Dodatni pribor	
LED driver, 700mA, 19-35W, dimabilan	LI1001132
TCI LED-Driver 50VA, 350-1050mA Dip-Switch, DALI- dim. inkl. Cable relief	LI464032
LED-Driver, 40W, 700mA	LI464168