




Tehnički list za artikl: LI230100--

## DASAR T5-14 podni profil, T5 14W G5



### Tehnički podaci

|                    |                          |
|--------------------|--------------------------|
| Neto duljina (mm)  | 700,00                   |
| Neto širina (mm)   | 120,00                   |
| Neto masa (kg)     | 5,79                     |
| Otvor (mm)         | 680x125                  |
| Vrsta svjetiljke   | recessed floor luminaire |
| Način montaže      | Podna ugradna            |
| Boja               | inox                     |
| Materijal          | Aluminij<br>INOX         |
| Proizvođač         | 03-SLV                   |
| Kut svjetlosti (°) | 90                       |
| Pogonski uređaj    | EVG                      |
| Radni napon AC (V) | 230                      |
| Izvor svjetla      | fluorescent lamp Ø16mm   |
| Grlo               | G5                       |
| Snaga (W)          | 14                       |
| Broj svjetiljki    | 1                        |
| Klasa zaštite      | I                        |
| IP stupanj zaštite | IP67                     |
| Energetska klasa   | A2                       |

## Tehnički podaci - nastavak

|                     |         |
|---------------------|---------|
| Ugradna dubina (mm) | 110     |
| OTVOR mm            | 680x125 |

## Tablica artikla

| OPIS                                | KAT. BROJ |
|-------------------------------------|-----------|
| DASAR T5-14 podni profil, T5 14W G5 | LI230100  |
| <b>Dodatni pribor</b>               |           |
| T5 fluo cijev 14W, 3000K            | LI548014  |