


Tehnički list za artikl: LI70113060

AOT-O ML 42W 5000lm 4000K, IP50, PMMA opal, bijela, L-1250mm

Podesiva snaga: 27W (3200lm) / 42W (5000lm); 119lm/W



Krivulja raspodjele svjetla




Tehnički podaci

Neto duljina (mm)	1.260,00
Neto širina (mm)	105,00
Neto visina (mm)	87,00
Neto masa (kg)	2,30
Min. temperatura okoline (°C)	-20
Maks. temperatura okoline (°C)	25
Vrsta svjetiljke	Okrugle industrijske svjetiljke

Tehnički podaci - nastavak

Način montaže	Stropna Stropna nadgradna
Radna temperatura (°C)	-20 do +25
Boja	bijela
Materijal	PMMA Čelični lim
Pokrov	Opal
Kut svjetlosti (°)	120
Faktor odsjaja (UGR)	25
Pogonski uređaj	LED driver AC / DC
Radni napon AC (V)	220-240
Grlo	LED Platine
Efikasnost sustava (lm/W)	119
Snaga (W)	42
Boja svjetla	Neutralno bijela
Temperatura boje (K)	4000
Faktor uzvrata boje	≥80
Stabilnot boje MacAdam (sdcm)	3
Svjetlosni tok (lm)	3200/5000
Životni vijek	50.000h (L80/B10)
Dimabilno	Ne
Klasa zaštite	I
IP stupanj zaštite	IP50
Otpornost na udarce	IK02
(DxŠxV) mm	1260x105x87

Mjerne skice: AOT-O ML 42W 5000lm 4000K, IP50, PMMA opal, bijela, L-1250mm



Tablica artikla

OPIS	KAT. BROJ
AOT-O ML 42W 5000lm 4000K, IP50, PMMA opal, bijela, L-1250mm Podesiva snaga: 27W (3200lm) / 42W (5000lm); 119lm/W	LI70113060
Dodatni pribor	
Pokrov RWA0 136 opal	LI44970040