

Tehnički list za artikl: LI70123060

# AOT-O ML 55W 6600lm 4000K, IP50, PMMA opal, bijela, L-1550mm

Podesiva snaga: 43W (5100lm) / 55W (6600lm); 120lm/W



## Krivulja raspodjele svjetla




## Tehnički podaci

|                                |                                 |
|--------------------------------|---------------------------------|
| Neto duljina (mm)              | 1.560,00                        |
| Neto širina (mm)               | 105,00                          |
| Neto visina (mm)               | 87,00                           |
| Neto masa (kg)                 | 2,70                            |
| Min. temperatura okoline (°C)  | -20                             |
| Maks. temperatura okoline (°C) | 25                              |
| Vrsta svjetiljke               | Okrugle industrijske svjetiljke |

## Tehnički podaci - nastavak

|                               |                              |
|-------------------------------|------------------------------|
| Način montaže                 | Stropna<br>Stropna nadgradna |
| Radna temperatura (°C)        | -20 do +25                   |
| Boja                          | bijela                       |
| Materijal                     | PMMA<br>Čelični lim          |
| Pokrov                        | Opal                         |
| Kut svjetlosti (°)            | 120                          |
| Faktor odsjaja (UGR)          | 25                           |
| Pogonski uređaj               | LED driver AC / DC           |
| Radni napon AC (V)            | 220-240                      |
| Grlo                          | LED Platine                  |
| Efikasnost sustava (lm/W)     | 120                          |
| Snaga (W)                     | 55                           |
| Boja svjetla                  | Neutralno bijela             |
| Temperatura boje (K)          | 4000                         |
| Faktor uzvrata boje           | ≥80                          |
| Stabilnot boje MacAdam (sdcm) | 3                            |
| Svjetlosni tok (lm)           | 5100/6600                    |
| Životni vijek                 | 50.000h (L80/B10)            |
| Dimabilno                     | Ne                           |
| Klasa zaštite                 | I                            |
| IP stupanj zaštite            | IP50                         |
| Otpornost na udarce           | IK02                         |
| (DxŠxV) mm                    | 1560x105x87                  |

### Mjerne skice: AOT-O ML 55W 6600lm 4000K, IP50, PMMA opal, bijela, L-1550mm



## Tablica artikla

| OPIS                                                                                                                 | KAT. BROJ  |
|----------------------------------------------------------------------------------------------------------------------|------------|
| AOT-O ML 55W 6600lm 4000K, IP50, PMMA opal, bijela, L-1550mm<br>Podesiva snaga: 43W (5100lm) / 55W (6600lm); 120lm/W | LI70123060 |
| <b>Dodatni pribor</b>                                                                                                |            |
| Pokrov RWA0 158 opal                                                                                                 | LI45000040 |