


Tehnički list za artikl: LID13120--

Valo Small LED Track spot, 25W, 4000K, 1750lm, IP20, bijela **€CONOMY**

3-phase track spot




Tehnički podaci

Vrsta svjetiljke	Zidna nadgradna svjetiljka
Način montaže	Zidna nadgradna
Boja	bijela
Materijal	Aluminij Staklo
Pokrov	Bistri
Proizvođač	06-One Light
Kut svjetlosti (°)	36
Pogonski uređaj	LED Driver
Radni napon AC (V)	100-240
Ulazni napon AC (V)	100-240
Izlazni napon (V)	28
Izlazna struja (A)	0,70
Izvor svjetla	COB LED

Tehnički podaci - nastavak

Grlo	LED Platine
Snaga (W)	30
Boja svjetla	Neutralno bijela
Temperatura boje (K)	4000
Faktor uzvrata boje	≥80
Svjetlosni tok (lm)	2300
Broj svjetiljki	1
Životni vijek	30000
Klasa zaštite	I
IP stupanj zaštite	IP20
Energetska klasa	A
Izvor svj. uklj.	Da
(DxŠxV) mm	154x154x207
Neto duljina (mm)	154,00
Neto širina (mm)	154,00
Neto visina (mm)	207,00
Neto masa (kg)	1,17
System efficiency (lm/W)	77

Mjerne skice: Valo Small LED Track spot, 25W, 4000K, 1750lm, IP20, bijela



Tablica artikla

OPIS	KAT. BROJ
Valo Small LED Track spot, 25W, 4000K, 1750lm, IP20, bijela	LID13120
3-phase track spot	
Dodatni pribor	
3-fazna nadgradna šina duljine 3 metra, 16A, bijela	LID10812
3-phase power track system, series BLUE LINE	