


Tehnički list za artikl: LID13806--

Rolo-CL medium E27 75W, aluminij, antracit **ECONOMY**

Outdoor Ceiling Luminaire; 12 WALL & CEILING



Info o proizvodu

20W PAR30 E27 Die Cast, PAR30 Outdoor Cylinders. Complies with standard EN60598-1 and any other specific standards




Tehnički podaci

Dimabilno	Ovisno o izvoru svjetla Da
Klasa zaštite	I
IP stupanj zaštite	IP54
Vrsta svjetiljke	Stropne nadgradne svjetiljke
Izvor svjetla	Visokonaponska halogena žarulja sa odsijačem LED Retrofit
Izvor svj. uklj.	Ne
Broj svjetiljki	1
Grlo	E27
Snaga (W)	20

Tehnički podaci - nastavak

Radni napon AC (V)	100-240
Ulazni napon AC (V)	100-240
Frekvencija (Hz)	50/60
Način montaže	Stropna nadgradna
Boja	antracit
Materijal	Aluminij tlačni lijev
Visina (mm)	140
Promjer (mm)	108
Dodatni pribor	LIMD0027--; LID 13012--; LID 14500--; LID 16949--; LID 13106--
Potrebni pribor	LID 14499--
ØxV mm	106x 134

Mjerne skice: Rolo-CL medium E27 75W, aluminij, antracit



Tablica artikla

OPIS	KAT. BROJ
Rolo-CL medium E27 75W, aluminij, antracit Outdoor Ceiling Luminaire; 12 WALL & CEILING	LID13806
Potrebni pribor	
LED žarulja PAR30, 10W, E27, 3000K, 700lm, 230V, 40° 25 LAMPS	LID14499
Dodatni pribor	
LED Classic 8,8W 4000K 806lm E27 A60 270° senzor dnevne svjetlosti	LIMD0027
LED žarulja, mat, E27, 10,5W, 2700K, 806lm 25 LAMPS	LID13012
LED žarulja PAR30, 10W, E27, 4000K, 750lm, 230V, 40° 25 LAMPS	LID14500
Konektor 32A 2x3-port 26 ACCES&GADGETS	LID16949
Panik modul za GU10 LED 3-8,5W 3h This kit will also operate with GU10 LED lamps suitable for 180V DC power supply (Emergency); 22 EMERGENCY LIGHTS	LID13106