

Tehnički list za artikl: LID13987--

Sutil Round LED 30W, 4000K, 2100lm, 120°, IP40, bijele boje **ECONOMY**

complete with driver; 06 DOWNLIGHT FIX LED



Info o proizvodu

30W slim downlight LED, IP40, ideal for commercial applications such as offices, galleries and showrooms. Supplied with 700mA non-dimmable LED driver. Complies with standard EN60598-1 and any other specific standards.




Tehnički podaci

Svjetlosni tok (lm)	2100
Boja svjetla	Hladno bijela
Temperatura boje (K)	4000
Faktor uzvrata boje	≥80
Životni vijek	30.000h
Dimabilno	Ne
Klasa zaštite	II
IP stupanj zaštite	IP40
Vrsta svjetiljke	LED Panel
Izvor svj. uklj.	Da

Tehnički podaci - nastavak

Broj svjetiljki	1
Grlo	LED Platine
Kut svjetlosti (°)	120
Efikasnost sustava (lm/W)	70
Faktor snage	0,9
Snaga (W)	30
Pogonski uređaj	LED Driver
Radni napon AC (V)	220-240
Frekvencija (Hz)	50/60
Način montaže	Stropna ugradna
Otvor (mm)	Ø 285
Ugradna dubina (mm)	50
Boja	bijela
Materijal	Plastika Akril Aluminij tlačni lijev
Visina (mm)	22
Promjer (mm)	295
Dodatni pribor	LID 16598--
ØxV mm	295x22
OTVOR mm	Ø 285

Mjerne skice: Sutil Round LED 30W, 4000K, 2100lm, 120°, IP40, bijele boje



Tablica artikla

OPIS	KAT. BROJ
Sutil Round LED 30W, 4000K, 2100lm, 120°, IP40, bijele boje complete with driver; 06 DOWNLIGHT FIX LED	LID13987
Dodatni pribor	
LED driver 230V 8-50W 1500mA DALI dimmable IP20 230V; 23 DRIVERS	LID16598