


Tehnički list za artikl: LID14068--

Mara-I-R LED 25W 3000K 1800lm, IP54, bije le boje **€ECONOMY**

13 WALL & CEIL LED



Krivulja raspodjele svjetla



Info o proizvodu

25W COB LED cylinder, IP54, suitable for indoor and outdoor installation. Complete with non-dimmable LED driver. Complies with standard EN60598-1 and any other specific standards.



Tehnički podaci

Svjetlosni tok (lm)	1800
---------------------	------

Tehnički podaci - nastavak

Boja svjetla	Toplo bijela
Temperatura boje (K)	3000
Faktor uzvrata boje	≥80
Dimabilno	Ne
Klasa zaštite	I
IP stupanj zaštite	IP54
Vrsta svjetiljke	Stropne nadgradne svjetiljke
Izvor svj. uklj.	Da
Broj svjetiljki	1
Grlo	LED Platine
Kut svjetlosti (°)	60
Efikasnost sustava (lm/W)	72
Faktor snage	0,9
Snaga (W)	25
Pogonski uređaj	LED Driver
Radni napon AC (V)	100-240
Ulazni napon AC (V)	100-240
Pogonska struja mA (mA)	600
Frekvencija (Hz)	50/60
Način montaže	Stropna nadgradna
Boja	bijela
Materijal	Aluminij
Visina (mm)	120
Promjer (mm)	160
Dodatni pribor	LID16949--
ØxV mm	120x160

Mjerne skice: Mara-I-R LED 25W 3000K 1800lm, IP54, bijele boje

Tablica artikla

OPIS	KAT. BROJ
Mara-I-R LED 25W 3000K 1800lm, IP54, bijele boje 13 WALL & CEIL LED	LID14068
Dodatni pribor	
Konektor 32A 2x3-port 26 ACCES&GADGETS	LID16949