


Tehnički list za artikl: LID14511--

Zoe Q LED 3W, 3000K, 120lm, 350mA, IP54, aluminij **€CONOMY**

recessed wall luminaire, without driver; 19 WALL REC & INGRND



Info o proizvodu

3W 350mA LED wall recessed light, IP54, ideal for both indoor and outdoor installation. Requires 350mA driver. Supplied with box for concrete installation. Complies with standard EN60598-1 and any other specific standards.



Tehnički podaci

Svjetlosni tok (lm)	120
Boja svjetla	Toplo bijela
Temperatura boje (K)	3000
Faktor uzvrata boje	≥90
Dimabilno	Ovisno o driveru Da
Klasa zaštite	III
IP stupanj zaštite	IP54
Vrsta svjetiljke	Zidna ugradna svjetiljka

Tehnički podaci - nastavak

Izvor svj. uklj.	Da
Grlo	LED Platine
Kut svjetlosti (°)	24
Efikasnost sustava (lm/W)	40
Snaga (W)	3
Pogonski uređaj	Needs to be ordered separately
Pogonska struja mA (mA)	350
Ulazna struja (A)	0,35
Način montaže	Zidna ugradna
Otvor (mm)	Ø 49
Ugradna dubina (mm)	110 (zement), 70 (gips)
Boja	aluminij
Materijal	Aluminij
Duljina (mm)	56
Širina (mm)	56
Visina (mm)	54
Dodatni pribor	LID16949--
Potrebni pribor	LID13677--; LID16462--;
(DxŠxV) mm	56x56x54
OTVOR mm	Ø 49

Mjerne skice: Zoe Q LED 3W, 3000K, 120lm, 350mA, IP54, aluminij



Tablica artikla

OPIS	KAT. BROJ
Zoe Q LED 3W, 3000K, 120lm, 350mA, IP54, aluminij recessed wall luminaire, without driver; 19 WALL REC & INGRND	LID14511
Potrebni pribor	
89004, DRIVER 350mA 1-4W LED IP66 100-240V 23 DRIVERS	LID13677
LED driver 230V 2-4W 350mA dimabilni 23 DRIVERS	LID16462
Dodatni pribor	
Konektor 32A 2x3-port 26 ACCES&GADGETS	LID16949