


Tehnički list za artikl: LID14545--

Moon S LED 6W, 3000K, 550lm, 100-240V, IP65, bijele boje **ECONOMY**

recessed wall luminaire; 19 WALL REC & INGRND



Info o proizvodu

7W LED wall recessed light, IP65, ideal for both indoor and outdoor installation. Complete 350mA driver. Supplied with box for concrete installation. Complies with standard EN60598-1 and any other specific standards.



Tehnički podaci

Svjetlosni tok (lm)	550
Boja svjetla	Toplo bijela
Temperatura boje (K)	3000
Faktor uzvrata boje	≥80
Dimabilno	Ne
Klasa zaštite	I
IP stupanj zaštite	IP65
Otpornost na udarce	IK06
Vrsta svjetiljke	Zidna ugradna svjetiljka
Izvor svj. uklj.	Da

Tehnički podaci - nastavak

Grlo	LED Platine
Efikasnost sustava (lm/W)	91
Faktor snage	0,5
Snaga (W)	7
Pogonski uređaj	LED Driver
Radni napon AC (V)	100-240
Ulazni napon AC (V)	100-240
Pogonska struja mA (mA)	350
Ulazna struja (A)	0,35
Frekvencija (Hz)	50/60
Način montaže	Zidna ugradna
Otvor (mm)	220x70
Ugradna dubina (mm)	80
Boja	bijela
Materijal	Aluminij tlačni lijev
Duljina (mm)	225
Širina (mm)	75
Visina (mm)	55
Dodatni pribor	LID16949--
(DxŠxV) mm	225x75x55
OTVOR mm	220x70

Mjerne skice: Moon S LED 6W, 3000K, 550lm, 100-240V, IP65, bijele boje



Tablica artikla

OPIS	KAT. BROJ
Moon S LED 6W, 3000K, 550lm, 100-240V, IP65, bijele boje recessed wall luminaire; 19 WALL REC & INGRND	LID14545
Dodatni pribor	
Konektor 32A 2x3-port 26 ACCES&GADGETS	LID16949