

Tehnički list za artikl: LID14848--

Tina LED, 12W, 700mA, 1100lm, 3000K, 38°, IP65 , crne boje

potreban 700mA driver



Info o proizvodu

12W COB LED recessed spot, IP65, for general application. Suitable for bathroom installation. Requires 700mA constant current driver. Complies with standard EN60598-1 and any other specific standards.

Tehnički podaci

Svjetlosni tok (lm)	1100
Boja svjetla	Toplo bijela
Temperatura boje (K)	3000
Faktor uzvrata boje	≥90
Dimabilno	Ovisno o driveru Da
Klasa zaštite	III
IP stupanj zaštite	IP65
Vrsta svjetiljke	Stropne ugradne svjetiljke
Izvor svj. uklj.	Da
Grlo	LED Platine
Kut svjetlosti (°)	38
Efikasnost sustava (lm/W)	91

Tehnički podaci - nastavak

Snaga (W)	12
Pogonski uređaj	Needs to be ordered separately
Pogonska struja mA (mA)	700
Ulazna struja (A)	0,70
Način montaže	Stropna ugradna
Otvor (mm)	Ø 75
Ugradna dubina (mm)	110
Boja	crna
Materijal	Aluminij tlačni lijev
Promjer (mm)	83
Dodatni pribor	LID16949--
Potrebni pribor	LID13081--;
ØxV mm	82x100
OTVOR mm	Ø 75

Mjerne skice: Tina LED, 12W, 700mA, 1100lm, 3000K, 38°, IP65 , crne boje



Tablica artikla

OPIS	KAT. BROJ
Tina LED, 12W, 700mA, 1100lm, 3000K, 38°, IP65 , crne boje potreban 700mA driver	LID14848
Potrebni pribor	
LED Driver 700mA, 7-15W, ulaz 220-240V 23 DRIVERS	LID13081
Dodatni pribor	
Konektor 32A 2x3-port 26 ACCES&GADGETS	LID16949