

Tehnički list za artikl: LID14849--

Sutil Round2 LED 8W, 3000K, 560lm, 120°, IP40, crne boje

ugradni downlight, uključen driver



Info o proizvodu

8W slim downlight LED, IP40, ideal for commercial applications such as offices, galleries and showrooms. Supplied with 300mA non-dimmable LED driver. Complies with standard EN60598-1 and any other specific standards.

Tehnički podaci

Svjetlosni tok (lm)	480
Boja svjetla	Toplo bijela
Temperatura boje (K)	3000
Faktor uzvrata boje	≥80
Životni vijek	30.000h
Dimabilno	Ne
Klasa zaštite	II
IP stupanj zaštite	IP40
Izvor svj. uklj.	Da
Grlo	LED Platine
Kut svjetlosti (°)	120
Efikasnost sustava (lm/W)	60

Tehnički podaci - nastavak

Faktor snage	0,6
Snaga (W)	8
Pogonski uređaj	LED Driver
Radni napon AC (V)	220-240
Frekvencija (Hz)	50/60
Način montaže	Stropna ugradna
Otvor (mm)	Ø 108
Ugradna dubina (mm)	50
Boja	crna
Materijal	Plastika Akril Aluminij tlačni lijev
Promjer (mm)	120
Dodatni pribor	LID16949--
OTVOR mm	Ø 108

Mjerne skice: Sutil Round2 LED 8W, 3000K, 560lm, 120°, IP40, crne boje



Tablica artikla

OPIS	KAT. BROJ
Sutil Round2 LED 8W, 3000K, 560lm, 120°, IP40, crne boje ugradni downlight, uključen driver	LID14849
Dodatni pribor	
Konektor 32A 2x3-port 26 ACCES&GADGETS	LID16949