

Tehnički list za artikl: LID15501--

# Alhema II LED 48W, 4200lm, 3000K, 230V, IP20, bijele b.

stropna ili ovjesna (uz pribor) svjetiljka, uključen driver



## Info o proizvodu

48W LED fitting ideal for office installation, IP20. Supplied with non-dimmable LED driver. Complies with standard EN60598-1 and any other specific standards.

## Tehnički podaci

|                           |                                          |
|---------------------------|------------------------------------------|
| Svjetlosni tok (lm)       | 4200                                     |
| Boja svjetla              | Toplo bijela                             |
| Temperatura boje (K)      | 3000                                     |
| Faktor uzvrata boje       | ≥80                                      |
| Dimabilno                 | Ne                                       |
| Klasa zaštite             | II                                       |
| IP stupanj zaštite        | IP20                                     |
| Vrsta svjetiljke          | Stropne svjetiljke<br>pendulum luminaire |
| Izvor svj. uklj.          | Da                                       |
| Grlo                      | LED Platine                              |
| Efikasnost sustava (lm/W) | 88                                       |
| Snaga (W)                 | 48                                       |

## Tehnički podaci - nastavak

|                    |                              |
|--------------------|------------------------------|
| Pogonski uređaj    | LED Driver                   |
| Radni napon AC (V) | 220-240                      |
| Frekvencija (Hz)   | 50/60                        |
| Način montaže      | Ovjesna<br>Stropna nadgradna |
| Boja               | bijela                       |
| Materijal          | Plastika<br>Aluminij         |
| Duljina (mm)       | 1215                         |
| Širina (mm)        | 130                          |
| Visina (mm)        | 27                           |
| Dodatni pribor     | LID 14827--;                 |
| (DxŠxV) mm         | 1215x130x27                  |

## Mjerne skice: Alhema II LED 48W, 4200lm, 3000K, 230V, IP20, bijele b.

 = 27mm

## Tablica artikla

| OPIS                                                                                                                                 | KAT. BROJ |
|--------------------------------------------------------------------------------------------------------------------------------------|-----------|
| Alhema II LED 48W, 4200lm, 3000K, 230V, IP20, bijele b.<br>stropna ili ovjesna (uz pribor) svetiljka, uključen driver                | LID15501  |
| <b>Dodatni pribor</b>                                                                                                                |           |
| Ovjesni pribor 1450mm za svj. serije Kylo, Yoda, Anakin<br>FOR 38120L/38135L/38248L/38225M/38248M/38250M/38236D; 11 OFFICE & KITCHEN | LID14827  |