

Tehnički list za artikl: LID15827--

Giro D8 GU10 50W 220-240V IP20 bijelo/ zlatne boje

ugradna spot svjetiljka



Tehnički podaci

Dimabilno	Ovisno o izvoru svjetla Da
Klasa zaštite	I
IP stupanj zaštite	IP20
Izvor svjetla	LED Retrofit MR16
Izvor svj. uklj.	Ne
Broj svjetiljki	1
Grlo	GU10
Snaga (W)	10
Radni napon AC (V)	100-240
Pogonska struja mA (mA)	
Frekvencija (Hz)	50/60
Način montaže	Stropna ugradna
Otvor (mm)	Ø62
Ugradna dubina (mm)	130

Tehnički podaci - nastavak

Boja	bijela zlatna
Materijal	Aluminij
Visina (mm)	50
Promjer (mm)	68
Dodatni pribor	LID 17278--; LID 17279--; LID 17203--; LID 13226--; LID 14508--; LID 15671--; LID 16949--; LID 16223--; LID 13106--
ØxV mm	68x50
OTVOR mm	Ø62

Tablica artikla

OPIS	KAT. BROJ
Giro D8 GU10 50W 220-240V IP20 bijelo/zlatne boje ugradna spot svjetiljka	LID 15827
Dodatni pribor	
LED 5W GU10 500lm 3000K CRI80 IP44 230V 38° Suitable for high ambient temperature enclosed fittings	LID 17278
LED 5W GU10 500lm 3000K CRI80 IP44 230V 38° dimabilna Suitable for high ambient temperature enclosed luminaires	LID 17279
LED 4W 300lm 3000K GU10 60° CRI90 TRIAC dimabilna 230V EM 3h	LID 17203
COB LED GU10, 6W, 3000K, 500lm, 60°, 230V	LID 13226
LED žarulja MR16, 6W, GU10, 3000K, 500lm, 230V, 60°, dimabilna dimabilna	LID 14508
LED GU10 MR16 6W 500lm 3000K 60° 230V crne boje Reflector lamp	LID 15671
Konektor 32A 2x3-port	LID 16949
EM driver 3H MR16 LED modul 3W 3 230V IP20 0	LID 16223
Panik modul za GU10 LED 3-8,5W 3h This kit will also operate with GU10 LED lamps suitable for 180V DC power supply (Emergency)	LID 13106