

Tehnički list za artikl: LID16449--

Ithaca LED 9W 675lm 3000K Ra90 IP20, bijele boje

ugradna svjetiljka, potreban 500mA driver



Info o proizvodu

9W COB LED recessed spot IP20. _x000D_ Requires 500mA driver. _x000D_ Complete with Black & Brass reflectors. _x000D_ Complies with standard EN60598-1 and any other specific standards.

Tehnički podaci

Svjetlosni tok (lm)	675
Boja svjetla	Toplo bijela
Temperatura boje (K)	3000
Faktor uzvrata boje	≥90
Dimabilno	Ovisno o driveru Da
Klasa zaštite	III
IP stupanj zaštite	IP20
Vrsta svjetiljke	Stropne ugradne svjetiljke
Izvor svj. uklj.	Da
Grlo	LED Platine
Kut svjetlosti (°)	40
Efikasnost sustava (lm/W)	75

Tehnički podaci - nastavak

Snaga (W)	9
Pogonski uređaj	Needs to be ordered separately
Pogonska struja mA (mA)	550
Ulazna struja (A)	0,50
Način montaže	Stropna ugradna
Otvor (mm)	Ø 120
Ugradna dubina (mm)	90
Boja	bijela
Materijal	Aluminij
Visina (mm)	134
Promjer (mm)	136
Dodatni pribor	LID16949--
Potrebni pribor	LID15950--; LID16616--;
ØxV mm	136x134
OTVOR mm	Ø 120

Mjerne skice: Ithaca LED 9W 675lm 3000K Ra90 IP20, bijele boje



Klasa energetske efikasnosti: Ithaca LED 9W 675lm 3000K Ra90 IP20, bijele boje



Tablica artikla

OPIS	KAT. BROJ
Ithaca LED 9W 675lm 3000K Ra90 IP20, bijele boje ugradna svjetiljka, potreban 500mA driver	LID16449
Potrebni pribor	
LED driver 7,5 - 15W 230V 500mA IP20 23 DRIVERS	LID15950
LED Driver 500mA 7,5-15W 230V 23 DRIVERS	LID16616
Dodatni pribor	
Konektor 32A 2x3-port 26 ACCES&GADGETS	LID16949