

Tehnički list za artikl: LIMQ1E805A

M48 Area QU-D 1 Modul 48LEDs 4000K IP66 114W 10775lm RAL9006

Version with 1 Module 48LEDs - SK.II - Power of luminaire 114W with Lumen output 10.775lm @700mA, Power of luminaire 83W with lumen output 8.615lm @525mA, Power of luminaire 55W with lumen output 6.215lm @350mA - "Economy" Version (ON-OFF)



Tehnički podaci

Vrsta svjetiljke	high-bay reflector luminaire
Način montaže	Ovjesna Stropna nadgradna
Boja	RAL 9006 (siva)
Materijal	Aluminij
Pogonski uređaj	LED Driver
Nazivni napon (V)	230
Izvor svjetla	LED
Grlo	LED Platine
Snaga (W)	114
Boja svjetla	Neutralno bijela
Temperatura boje (K)	4000
Faktor uzvrata boje	≥70
Svjetlosni tok (lm)	10775

Tehnički podaci - nastavak

Broj svjetiljki	1
Klasa zaštite	II
IP stupanj zaštite	IP66
Izvor svj. uklj.	Da
(DxŠxV) mm	495x175x65

Tablica artikla

OPIS	KAT. BROJ
M48 Area QU-D 1 Modul 48LEDs 4000K IP66 114W 10775lm RAL9006	
Version with 1 Module 48LEDs - SK.II - Power of luminaire 114W with Lumen output 10.775lm @700mA, Power of luminaire 83W with lumen output 8.615lm @525mA, Power of luminaire 55W with lumen output 6.215lm @350mA - "Economy" Version (ON-OFF)	
Dodatni pribor	
Stropni nosač za M48 Area RAL9006	LI06MQ900A
Pribor za ovjes za M48, duljina= 1,5m	LI06MQ901J