

Tehnički list za artikl: LITP0054--


LANO BL LED 33W 840 4400lm 850mA M625

UGR<19 mikroprizma

LED Backlit Panel, može se kombinirati sa LED driverom LITP0029 (on/off) ili LITP0030-A (DALI, Push Dim)



Krivulja raspodjele svjetla




Tehnički podaci

Neto duljina (mm)	620,00
Neto širina (mm)	620,00
Neto visina (mm)	30,00
Neto masa (kg)	2,05

Tehnički podaci - nastavak

Min. temperatura okoline (°C)	-20
Maks. temperatura okoline (°C)	40
Vrsta svjetiljke	LED Panel
Način montaže	Ugradna za panel stropove Stropna ugradna Stropna nadgradna
Boja	bijela
Materijal	Čelični lim
Faktor odsjaja (UGR)	< 19
Pogonska struja mA (mA)	850
Efikasnost sustava (lm/W)	135lm/w
Snaga (W)	33
Boja svjetla	Neutralno bijela
Temperatura boje (K)	4000
Faktor uzvrata boje	≥80
Stabilnot boje MacAdam (sdc _m)	≤3
Svjetlosni tok (lm)	4300
Životni vijek	50.000h / L70 / B50
Dimabilno	Ovisno o driveru Da
Klasa zaštite	III
IP stupanj zaštite	IP20, IP40 optical part
Izvor svj. uklj.	Da
(DxŠxV) mm	620x620x30

Mjerne skice: LANO BL LED 33W 840 4400lm 850mA M625 UGR<19 mikroprizma**Tablica artikla**

OPIS	KAT. BROJ
LANO BL LED 33W 840 4400lm 850mA M625 UGR<19 mikroprizma	LITP0054
LED Backlit Panel, može se kombinirati sa LED driverom LITP0029 (on/off) ili LITP0030-A (DALI, Push Dim)	
Dodatni pribor	
LED Driver 33W 850mA on/off za seriju Lano 4 LED	LITP0029
LED Driver DALI-2 33W 850mA za Seriju Lano 4 LED	LITP0030-A
DALI und Push Dim	
3-polna spojna kutija, IP20, Quick Fix	LID15379
EM modul 3H za LED Panel Lano 4 30-40W	LITP0032