

Tehnički list za artikl: LIVT4858--

12W LED Premium Panel Downlight - okrugli

4000K, 1000lm, 120° €CONOMY

including driver, quick connector




Tehnički podaci

(DxŠxV) mm	170x170x25
ØxV mm	170x25
OTVOR mm	Ø 155
Boja	bijela
Materijal	PS PMMA Aluminij
Način montaže	Stropna ugradna
Otvor (mm)	Ø 155
Snaga (W)	12
Radni napon AC (V)	200-240
Boja svjetla	Neutralno bijela
Svjetlosni tok (lm)	1000
Faktor snage	>0.6

Tehnički podaci - nastavak

Faktor uzvrata boje	≥80
Dimabilno	Ne
Temperatura boje (K)	4000
Životni vijek	20.000h
Kut svjetlosti (°)	120
IP stupanj zaštite	IP20
Klasa zaštite	II
Min. temperatura okoline (°C)	-20
Maks. temperatura okoline (°C)	45
Vrsta svjetiljke	LED Panel
Izvor svjetla	SMD LED
Grlo	LED Platine
Efikasnost sustava (lm/W)	83
Snaga (W)	12
Frekvencija (Hz)	60
Duljina (mm)	170
Širina (mm)	170
Visina (mm)	25
Promjer (mm)	170

Mjerne skice: 12W LED Premium Panel Downlight - okrugli 4000K, 1000lm, 120°



12W LED Premium Panel Downlight - okrugli 4000K, 1000lm, 120°
including driver, quick connector

LIVT4858