


Tehnički list za artikl: NLAXRW09EL

Svjet.design AX LED bijela 230V AC/DC, montaža u zid

Centrally switchable, with single lamp supervision, Viewing distance: 30m, 230V AC/DC




Tehnički podaci

Neto duljina (mm)	317,00
Neto širina (mm)	79,00
Neto visina (mm)	194,00
Neto masa (kg)	1,40
Vrsta svjetiljke	Panik svjetiljka
VB/CPS	Za centralni panik sustav (CPS)
Funkcija	S nadzorom - centralno ON/OFF
Izvedba/tip	Plosnate svjetiljke
Dizajn	AX
Boja	RAL 9003 (bijela)
Piktogram	Slide-in pictogram set (arrow left, right, bottom, top and white foil for single side use) included in accordance with ISO 7010
Područje detekcije (m)	30
Izvor svjetla	LED (3W)
Naponsko područje (V)	230V AC 50Hz ±20%; 230V DC ±20%
Power maintained mode (W)	4,50
Power non-maintained mode (W)	1,10
Power max. (W)	4,50
IP stupanj zaštite	IP40
Otpornost na udarce	≥ IK03
Način montaže	Zidna ugradna
Min. temperatura okoline (°C)	-5

Tehnički podaci - nastavak

Maks. temperatura okoline (°C)	40
AA Klasa E 8101	AA4
Proizvođač	Schrack

Dimensions (mm)



Tablica artikla

OPIS	KAT. BROJ
Svjet.design AX LED bijela 230V AC/DC, montaža u zid Centrally switchable, with single lamp supervision, Viewing distance: 30m, 230V AC/DC	NLAXRW09EL
Dodatni pribor	
Kutija za ugradnju u beton svjetiljke design AM/AX	NLAMAXBE