

Tehnički list za artikl: NLILER023S

Design IL ERT-LED 1x3W 230VAC 3h, ugradna, radijalno Autotest


White, surface ceiling mounting, for illuminating rescue routes with luminaire distance 8,9m at room height 4m



Tehnički podaci

Neto visina (mm)	95,00
Neto promjer (mm)	122,00
Neto masa (kg)	0,30
Vrsta svjetiljke	Sigurnosna svjetiljka
VB/CPS	Sa vlastitom baterijom
Funkcija	Samokontrola
Izvedba/tip	Plastične svjetiljke
Dizajn	IL
Bez halogena	Plastično kućište, bez halogena
Boja	bijela
Vrijeme autonomije (h)	3
Izvor svjetla	ERT-LED (3W)
Lumen	240
Napon (V)	230V AC 50Hz ±20%
Baterija (V/Ah)	4,8/2,0 NiMh
IP stupanj zaštite	IP20
Način montaže	Stropna ugradna
AA Class E 8101	AA4

Dimensions NLILE... (mm)



Distance table - min. illumination at the middle line: 1 lx - maintenance factor 0,80 -3h autonomy time

Montagehöhe [m]					
2,00	4.29	10.07	10.07	10.07	4.29
2,50	4.16	11.44	11.44	11.44	4.16
3,00	1.95	12.22	12.22	12.22	1.95
3,50	0,00	10.04	10.04	10.04	0,00
4,00	0,00	8,70	8,70	8,70	0,00

Tablica artikla

OPIS	KAT. BROJ
Design IL ERT-LED 1x3W 230VAC 3h, ugradna, radijalno Autotest	NLILR023S
White, surface ceiling mounting, for illuminating rescue routes with luminaire distance 8,9m at room height 4m	
Dodatni pribor	
Alat za lako otvaranje ugradnih svjetiljki tip IL	NLILTOOL
HSS Bi-metal cilindar pila (kruna), 105/36mm, bez adaptera	GI63290105
Kutija Ø170mm s klizačima i pločom od mineralnih valakana	GTDP422
Zaštita od lopte od pleksija Dim 190x190x62mm, Desing IL/EA	NLBALLPLX4
Thickness 5mm, recommended for NLIL.. surface mounted	
Zaštitna mreža za Design IL, KI, VI, RI, KT, DAQ, DAR	NLBALL3
Baterija 4,8V 2,0Ah za svjet. sa vl. nap. LED sa LPU modulom	NLAKKU4820
LPU or LEM module	