

# Emergency luminaire KW Autotest LED 3h 230V AC ceiling

1h/3h adjustable, ceiling surface mounting with pictograms on one or two sides or for wall surface mounting with pictogram on one side, viewing distance: 16m, IP54, protection class II, 1h: 300lm; 3h: 300lm




## Tehnički podaci

|                        |                                 |
|------------------------|---------------------------------|
| Neto duljina (mm)      | 390,00                          |
| Neto širina (mm)       | 93,00                           |
| Neto visina (mm)       | 139,00                          |
| Neto masa (kg)         | 1,30                            |
| Vrsta svjetiljke       | Panik svjetiljka                |
| VB/CPS                 | Sa vlastitom baterijom          |
| Funkcija               | Samokontrola                    |
| Izvedba/tip            | Plastične svjetiljke            |
| Dizajn                 | KW                              |
| Bez halogena           | Plastično kućište, bez halogena |
| Boja                   | bijela                          |
| Područje detekcije (m) | 16                              |

## Tehnički podaci - nastavak

|                                |                       |
|--------------------------------|-----------------------|
| Vrijeme autonomije (h)         | 3                     |
| Izvor svjetla                  | LED (3W)              |
| Lumen                          | 1h: 300;3h: 300       |
| Raspon napona (V)              | 230V AC 50Hz ±20%     |
| Baterija (V/Ah)                | 2x 3,2V/1,6Ah LiFePO4 |
| IP stupanj zaštite             | IP54                  |
| Način montaže                  | Stropna nadgradna     |
| Min. temperatura okoline (°C)  | -5                    |
| Maks. temperatura okoline (°C) | 40                    |
| AA Klasa E 8101                | AA4                   |
| Proizvođač                     | Schrack               |

## Mjerne skice: Emergency luminaire KW Autotest LED 3h 230V AC ceiling



## Abstandstabelle 1h, 3h Autonomie - Min. Beleuchtungsstärke: 1lx - Wartungsfaktor 0,80

| Montagehöhe [m] |  |  |  |  |  |
|-----------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 2,00            | 3,55                                                                                | 9,23                                                                                | 8,09                                                                                | 7,02                                                                                  | 2,74                                                                                  |
| 2,50            | 3,68                                                                                | 9,78                                                                                | 8,62                                                                                | 7,52                                                                                  | 2,84                                                                                  |
| 3,00            | 3,72                                                                                | 10,17                                                                               | 8,98                                                                                | 7,85                                                                                  | 2,86                                                                                  |
| 3,50            | 3,66                                                                                | 10,40                                                                               | 9,20                                                                                | 8,05                                                                                  | 2,79                                                                                  |
| 4,00            | 3,51                                                                                | 10,51                                                                               | 9,29                                                                                | 8,11                                                                                  | 2,61                                                                                  |
| 5,00            | 2,80                                                                                | 10,34                                                                               | 9,08                                                                                | 7,86                                                                                  | 1,84                                                                                  |

## Tablica artikla

| OPIS                                                                                                                                                                                                                                                                                | KAT. BROJ |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| Emergency luminaire KW Autotest LED 3h 230V AC ceiling<br>1h/3h adjustable, ceiling surface mounting with pictograms on one or two sides or for wall surface mounting with pictogram on one NLKWD401SC side, viewing distance: 16m, IP54, protection class II, 1h: 300lm; 3h: 300lm |           |
| <b>Dodatni pribor</b>                                                                                                                                                                                                                                                               |           |
| Zaštitna mrežica za panike KW                                                                                                                                                                                                                                                       | NLBKW     |
| Par cijevnih nosača 500mm, bijeli, montaža strop                                                                                                                                                                                                                                    | NL2PW     |
| Zidni metalni nosač panik lampi za KB,KX,KW,KCD,KE,GX,RX                                                                                                                                                                                                                            | NLAWX001  |