

Tehnički list za artikl: NLKWD403SC

Emergency luminaire KW Autotest LED 3h

230VAC stropna

Univerzalna montaža, sa 4x0.5W High Power LED, sa LiFePO4 baterijom integriranom, odabir autonomije 1h/3h, raspoznatljivost 30m; 1h:340lm, 3h:170lm




Tehnički podaci

Neto duljina (mm)	390,00
Neto širina (mm)	93,00
Neto visina (mm)	139,00
Neto masa (kg)	0,80
Vrsta svjetiljke	Panik svjetiljka
VB/CPS	Sa vlastitom baterijom
Funkcija	Samokontrola
Izvedba/tip	Plastične svjetiljke
Dizajn	KW
Bez halogena	Plastično kućište, bez halogena
Boja	bijela
Područje detekcije (m)	16
Vrijeme autonomije (h)	3

Tehnički podaci - nastavak

Izvor svjetla	LED (3W)
Lumen	1h: 300;3h: 300;8h: 120
Raspon napona (V)	230V AC 50Hz ±20%
Baterija (V/Ah)	2x 3,2V/1,6Ah LiFePO4
IP stupanj zaštite	IP54
Način montaže	Stropna nadgradna
Min. temperatura okoline (°C)	-5
Maks. temperatura okoline (°C)	40
AA Klasa E 8101	AA4
Proizvođač	Schrack

Mjerne skice: Emergency luminaire KW Autotest LED 3h 230VAC stropna



Abstandstabelle 1h, 3h Autonomie - Min. Beleuchtungsstärke: 1lx - Wartungsfaktor 0,80

Montagehöhe [m]					
2,00	3,55	9,23	8,09	7,02	2,74
2,50	3,68	9,78	8,62	7,52	2,84
3,00	3,72	10,17	8,98	7,85	2,86
3,50	3,66	10,40	9,20	8,05	2,79
4,00	3,51	10,51	9,29	8,11	2,61
5,00	2,80	10,34	9,08	7,86	1,84

Tablica artikla

OPIS	KAT. BROJ
Emergency luminaire KW Autotest LED 3h 230VAC stropna Univerzalna montaža, sa 4x0.5W High Power LED, sa LiFePO4 baterijom integriranom, odabir autonomije 1h/3h, raspoznatljivost NLKWD403SC 30m; 1h:340lm, 3h:170lm	
Dodatni pribor	
Zaštitna mrežica za panike KW	NLBKW
Par cijevnih nosača 500mm, bijeli, montaža strop	NL2PW
Zidni metalni nosač panik lampi za KB,KX,KW,KCD,KE,GX,RX	NLAWX001
Set 2x bat LiFePO4 3,2V 3,3Ah za WirelessControl svjetiljke LiFePO4 - Litij Željezo Fosfat baterija, norma UN3480	NLAKKU323L