

Tehnički list za artikl: NLMN102A--

Minikontrol centrala 2 kruga, 40 panik/ sigurnosnih svjetiljki

2 electrical circuits, max. 40 luminaires (20 luminaires per circuit), max. power rating: 1500 W 1 h / 500 W 3 h / 300 W 8 h, optionally expandable to max. 12 circuits max. 240 luminaires, h x w x d: 1100 x 500 x 230 mm



Tehnički podaci

Neto duljina (mm)	230,00
Neto širina (mm)	500,00
Neto visina (mm)	1.100,00
Neto masa (kg)	140,01

Tablica artikla

OPIS	KAT. BROJ
Minikontrol centrala 2 kruga, 40 panik/sigurnosnih svjetiljki 2 electrical circuits, max. 40 luminaires (20 luminaires per circuit), max. power rating: 1500 W 1 h / 500 W 3 h / 300 W 8 h, optionally expandable to max. 12 circuits max. 240 luminaires, h x w x d: 1100 x 500 x 230 mm	NLMN102A
Dodatni pribor	
E30 ormar vatrootporni za cent. MN s vent. DIM 1388x861x345 Outside dimensions: 1388 x 861 x 345mm (HxWxD), colour RAL7035, protection class II, IP54, 115kg, functional preservation 30 minutes - according to E30, fire resistance 30 minutes - according to F30/I30	NLMNE30
Pleksi vrata za Minikontrol centralu CPS-a	NLPLXMIN
Trofazni nadzor napona sa BUS vezom RS485	NLMCLM
Trofazni nadzor napona PC230	NLPC2300
SAM08 query modul 8 nezavisnih ulaza za isk/uklj rasvjete	NLSAM24
Vanjski pisač za CPS sustave Suitable for Micro-, Mini-, Midi-, Maxi- and MultiControl	NLBD04E
Nadzorna ploča sa LCD zaslonom, BUS komunikacija	NLMCT15
Nadzorna ploča sa LCD zaslonom, s ključem, BUS komunikacija With key switch	NLMCT15S