

Tehnički list za artikl: NLPMT03SC

# PM sigurnosna svj. LED 3h, 230V, SC, zidna montaža, TT

1h/3h/8h adjustable, wall surface mounting with pictograms, viewing distance: 20m, IP65, protection class II, LiFePO4 battery suitable for low temperatures -15° to 40°C



## Tehnički podaci

|                   |                                                                                                                           |
|-------------------|---------------------------------------------------------------------------------------------------------------------------|
| Neto duljina (mm) | 236,00                                                                                                                    |
| Neto širina (mm)  | 136,00                                                                                                                    |
| Neto visina (mm)  | 65,00                                                                                                                     |
| Neto masa (kg)    | 1,30                                                                                                                      |
| Vrsta svjetiljke  | Panik svjetiljka                                                                                                          |
| VB/CPS            | Sa vlastitom baterijom                                                                                                    |
| Funkcija          | SelfControl Low Temperature                                                                                               |
| Izvedba/tip       | Plastične svjetiljke                                                                                                      |
| Dizajn            | PM                                                                                                                        |
| Bez halogena      | Plastično kućište, bez halogena                                                                                           |
| Boja              | RAL 9003 (bijela)                                                                                                         |
| Piktogram         | Slide-in pictogram set (2x man in the door and one arrow that can be rotated by 90°) included in accordance with ISO 7010 |

## Tehnički podaci - nastavak

|                                |                          |
|--------------------------------|--------------------------|
| Područje detekcije (m)         | 20                       |
| Izvor svjetla                  | LED (3W)                 |
| Naponsko područje (V)          | 230V AC 50Hz ±20%        |
| Power maintained mode (W)      | 5,70                     |
| Power non-maintained mode (W)  | 2                        |
| Power max. (W)                 | 6,90                     |
| Baterija (V/Ah)                | 2x 3,2V/3,3Ah LiFePO4-TT |
| IP stupanj zaštite             | IP65                     |
| Otpornost na udarce            | IK06                     |
| Način montaže                  | Stropna                  |
| Min. temperatura okoline (°C)  | -15                      |
| Maks. temperatura okoline (°C) | 40                       |
| AA Klasa E 8101                | AA4                      |
| Proizvođač                     | Schrack                  |

## Dimensions (mm)



## Tablica artikla

| OPIS                                                                                                                                                                                                                                  | KAT. BROJ  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| PM sigurnosna svj. LED 3h, 230V, SC, zidna montaža, TT<br>1h/3h/8h adjustable, wall surface mounting with pictograms, viewing distance: 20m, IP65, protection class II, LiFePO4 battery<br>suitable for low temperatures -15° to 40°C | NLPMWT03SC |
| <b>Dodatni pribor</b>                                                                                                                                                                                                                 |            |
| Ugradni profil za svjetiljke serije PM<br>Required ceiling cut out: 246 x 152 mm                                                                                                                                                      | NLPME      |
| Baterija LiFePO4 3,2V 3,2Ah za svjetiljke KM,KSC,KMB,ASM,ZAW<br>LiFePO4 baterija prikladna za niže temperature, UN3480 - UN 3480 : Lithium-Ion batteries, od -25° do 40°C                                                             | NLAKKU323T |
|                                                                                                                                                                                                                                       | NLTESTSC2  |
| Zaštitni poklopac za testne tipke NLTEST2                                                                                                                                                                                             | NLTEST2COV |