

Tehnički list za artikl: NLPXW438WL

## PX WirelessControl 4x1 W ERT LED 8 h

Oznaka izlaza: nadgradna zidna montaža; sigurnosna rasvjeta: nadgradna stropna montaža; udaljenost prepoznavanja 30 m; bežično upravljanje; LiFePO4 baterija; 245 lm.



### Tehnički podaci

|                        |                                                                                                                           |
|------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Neto duljina (mm)      | 340,00                                                                                                                    |
| Neto širina (mm)       | 60,00                                                                                                                     |
| Neto visina (mm)       | 170,00                                                                                                                    |
| Neto masa (kg)         | 0,90                                                                                                                      |
| Vrsta svjetiljke       | Sigurnosna svjetiljka<br>Panik svjetiljka                                                                                 |
| VB/CPS                 | Sa vlastitom baterijom                                                                                                    |
| Funkcija               | WirelessControl Professional                                                                                              |
| Izvedba/tip            | Plastične svjetiljke                                                                                                      |
| Dizajn                 | PX                                                                                                                        |
| Bez halogena           | Plastično kućište, bez halogena                                                                                           |
| Boja                   | RAL 9003 (bijela)                                                                                                         |
| Piktogram              | Slide-in pictogram set (2x man in the door and one arrow that can be rotated by 90°) included in accordance with ISO 7010 |
| Područje detekcije (m) | 30                                                                                                                        |

## Tehnički podaci - nastavak

|                                |                                                                       |
|--------------------------------|-----------------------------------------------------------------------|
| Vrijeme autonomije (h)         | 3                                                                     |
| Izvor svjetla                  | ERT-LED (4W)                                                          |
| Lumen                          | 245                                                                   |
| Naponsko područje (V)          | 230V AC 50Hz ±20%                                                     |
| Power maintained mode (W)      | 5,70                                                                  |
| Power non-maintained mode (W)  | 0,80                                                                  |
| Power max. (W)                 | 7,50                                                                  |
| Baterija (V/Ah)                | 2x 3,2V/3,3Ah LiFePO4                                                 |
| IP stupanj zaštite             | IP65                                                                  |
| Otpornost na udarce            | IK05                                                                  |
| Način montaže                  | Stropna<br>Stropna ugradna opcija<br>Univerzalna<br>Stropna nadgradna |
| Min. temperatura okoline (°C)  | -5                                                                    |
| Maks. temperatura okoline (°C) | 40                                                                    |
| AA Klasa E 8101                | AA4                                                                   |
| Proizvođač                     | Schrack                                                               |

**Spacing table with square lens (for optimized illumination of the pictogram)  
(included in scope delivery) - Minimum illuminance on the centerline at +/- 0.5  
m: 1 lx - Maintenance factor 0.80 - Autonomy time 8h**

|                                                                                     |                                                                                     |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|  |  |  |  |  |  |
| 2,00                                                                                | 4,29                                                                                | 9,95                                                                                | 9,95                                                                                | 9,95                                                                                  | 4,29                                                                                  |
| 2,50                                                                                | 4,55                                                                                | 11,35                                                                               | 11,35                                                                               | 11,35                                                                                 | 4,55                                                                                  |
| 3,00                                                                                | 4,29                                                                                | 12,42                                                                               | 12,42                                                                               | 12,42                                                                                 | 4,29                                                                                  |
| 3,50                                                                                | 3,11                                                                                | 12,87                                                                               | 12,87                                                                               | 12,87                                                                                 | 3,11                                                                                  |
| 4,00                                                                                | 2,16                                                                                | 12,25                                                                               | 12,25                                                                               | 12,25                                                                                 | 2,16                                                                                  |

**Spacing table with corridor lens (NLLSYSF4 must be ordered separately) - Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 - Autonomy time 8h**

|  |  |  |  |  |  |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 2,00                                                                              | 4,93                                                                              | 10,84                                                                             | 8,98                                                                              | 7,23                                                                                | 2,84                                                                                |
| 2,50                                                                              | 5,84                                                                              | 13,01                                                                             | 10,28                                                                             | 7,84                                                                                | 2,97                                                                                |
| 3,00                                                                              | 6,67                                                                              | 14,99                                                                             | 11,54                                                                             | 8,22                                                                                | 3,03                                                                                |
| 3,50                                                                              | 7,22                                                                              | 16,82                                                                             | 12,58                                                                             | 8,48                                                                                | 2,99                                                                                |
| 4,00                                                                              | 5,37                                                                              | 18,52                                                                             | 13,5                                                                              | 8,63                                                                                | 2,94                                                                                |
| 5,00                                                                              | 3,93                                                                              | 17,81                                                                             | 11,74                                                                             | 8,46                                                                                | 2,8                                                                                 |
| 6,00                                                                              | 2,21                                                                              | 16,25                                                                             | 10,3                                                                              | 8,3                                                                                 | 2,25                                                                                |

**Spacing table with round lens (NLLSYSR4 must be ordered separately) - Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 - Autonomy time 8h**

|  |  |  |  |  |  |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 2,00                                                                              | 3,89                                                                              | 8,38                                                                              | 8,38                                                                              | 8,38                                                                                | 3,89                                                                                |
| 2,50                                                                              | 4,58                                                                              | 10,05                                                                             | 10,05                                                                             | 10,05                                                                               | 4,58                                                                                |
| 3,00                                                                              | 5,19                                                                              | 11,54                                                                             | 11,54                                                                             | 11,54                                                                               | 5,19                                                                                |
| 3,50                                                                              | 5,15                                                                              | 12,91                                                                             | 12,91                                                                             | 12,91                                                                               | 5,15                                                                                |
| 4,00                                                                              | 3,83                                                                              | 13,42                                                                             | 13,42                                                                             | 13,42                                                                               | 3,83                                                                                |
| 5,00                                                                              | 1,54                                                                              | 12,54                                                                             | 12,54                                                                             | 12,54                                                                               | 1,54                                                                                |

**Spacing table with spot lens (NLLSYSS4 must be ordered separately) - Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 - Autonomy time 8h**

|  |  |  |  |  |  |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| 2,00                                                                                | 1,91                                                                                | 4,79                                                                                | 4,79                                                                                | 4,79                                                                                  | 1,91                                                                                  |
| 2,50                                                                                | 2,31                                                                                | 5,8                                                                                 | 5,8                                                                                 | 5,8                                                                                   | 2,31                                                                                  |
| 3,00                                                                                | 2,53                                                                                | 6,08                                                                                | 6,08                                                                                | 6,08                                                                                  | 2,53                                                                                  |
| 3,50                                                                                | 2,78                                                                                | 6,57                                                                                | 6,57                                                                                | 6,57                                                                                  | 2,78                                                                                  |
| 4,00                                                                                | 3,02                                                                                | 7,04                                                                                | 7,04                                                                                | 7,04                                                                                  | 3,02                                                                                  |
| 5,00                                                                                | 3,41                                                                                | 7,99                                                                                | 7,99                                                                                | 7,99                                                                                  | 3,41                                                                                  |
| 6,00                                                                                | 3,75                                                                                | 8,91                                                                                | 8,91                                                                                | 8,91                                                                                  | 3,75                                                                                  |
| 7,00                                                                                | 3,98                                                                                | 9,64                                                                                | 9,64                                                                                | 9,64                                                                                  | 3,98                                                                                  |
| 8,00                                                                                | 4,1                                                                                 | 10,37                                                                               | 10,37                                                                               | 10,37                                                                                 | 4,1                                                                                   |
| 9,00                                                                                | 4,12                                                                                | 10,93                                                                               | 10,93                                                                               | 10,93                                                                                 | 4,12                                                                                  |
| 10,00                                                                               | 4,05                                                                                | 11,34                                                                               | 11,34                                                                               | 11,34                                                                                 | 4,05                                                                                  |
| 12,00                                                                               | 3,59                                                                                | 11,7                                                                                | 11,7                                                                                | 11,7                                                                                  | 3,59                                                                                  |
| 14,00                                                                               | 2,56                                                                                | 11,53                                                                               | 11,53                                                                               | 11,53                                                                                 | 2,56                                                                                  |

**Spacing table with high corridor lens (NLLSYSH4 must be ordered separately)**  
**- Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 -**  
**Autonomy time 8h**

|       |  |  |  |  |  |
|-------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| 2,00  | 2,2                                                                               | 5,84                                                                              | 7,56                                                                              | 9,25                                                                                | 4,02                                                                                |
| 2,50  | 2,27                                                                              | 6,2                                                                               | 8,38                                                                              | 10,56                                                                               | 4,66                                                                                |
| 3,00  | 2,27                                                                              | 6,4                                                                               | 9,19                                                                              | 11,98                                                                               | 5,22                                                                                |
| 3,50  | 2,19                                                                              | 6,5                                                                               | 9,87                                                                              | 13,25                                                                               | 5,61                                                                                |
| 4,00  | 1,95                                                                              | 6,5                                                                               | 10,45                                                                             | 14,4                                                                                | 5,95                                                                                |
| 5,00  | 1,77                                                                              | 6,28                                                                              | 11,23                                                                             | 16,18                                                                               | 6,41                                                                                |
| 6,00  | 1,83                                                                              | 5,31                                                                              | 11,34                                                                             | 17,46                                                                               | 6,67                                                                                |
| 7,00  | 1,81                                                                              | 5,01                                                                              | 11,53                                                                             | 18,35                                                                               | 6,6                                                                                 |
| 8,00  | 1,81                                                                              | 5,17                                                                              | 11,54                                                                             | 18,98                                                                               | 6,12                                                                                |
| 9,00  | 1,73                                                                              | 5,14                                                                              | 10,85                                                                             | 19,27                                                                               | 5,89                                                                                |
| 10,00 | 1,58                                                                              | 5,13                                                                              | 10,53                                                                             | 18,88                                                                               | 5,61                                                                                |
| 12,00 | 1,02                                                                              | 5,05                                                                              | 9,65                                                                              | 17,18                                                                               | 3,55                                                                                |

## Tablica artikla

| OPIS                                                                                                                                                                                                          | KAT. BROJ  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| PX WirelessControl 4x1 W ERT LED 8 h<br>Oznaka izlaza: nadgradna zidna montaža; sigurnosna rasvjeta: nadgradna stropna montaža; udaljenost prepoznavanja 30 m; bežično upravljanje; LiFePO4 baterija; 245 lm. | NLPXW438WL |
| <b>Dodatni pribor</b>                                                                                                                                                                                         |            |
| Poklopac za zaštitu od kiše za KC , pleksi                                                                                                                                                                    | NLKCRD     |
| Zaštitna mrežica za panike KC, KL, PF, S8<br>l x h x d: 450 x 280 x 125mm                                                                                                                                     | NLBALL2    |
| Piktogram set za NLPX.. 2x "invalid", 2x diag. strijelice<br>Dvodjelni piktogrami, raspoznatljivost do 30m                                                                                                    | NLPXPIKTO2 |
|                                                                                                                                                                                                               | NLTESTSC2  |
| Zaštitni poklopac za testne tipke NLTEST2                                                                                                                                                                     | NLTEST2COV |
| Set 2x bat LiFePO4 3,2V 3,3Ah za WirelessControl svjetiljke<br>LiFePO4 - Litij Željezo Fosfat baterija, norma UN3480                                                                                          | NLAKKU323L |