

Tehnički list za artikl: NLWXD003SC

design WX LED 1h/3h/8h odabir autonomije, stropna

Ceiling surface mounting or optional chain rope or pendant mounting, 1h/3h/8h adjustable; pictograms with arrows left, down, up are already mounted, viewing distance: 90m





Tehnički podaci

Neto duljina (mm)	500,00
Neto širina (mm)	500,00
Neto visina (mm)	500,00
Neto masa (kg)	1,50
Vrsta svjetiljke	Panik svjetiljka
VB/CPS	Sa vlastitom baterijom
Funkcija	Samokontrola
Izvedba/tip	Plastične svjetiljke
Dizajn	WX
Boja	bijela
Područje detekcije (m)	90
Vrijeme autonomije (h)	3
Izvor svjetla	LED (3W)
Raspon napona (V)	230V AC 50Hz ±20%
Baterija (V/Ah)	4,8/2,0 NiMH
IP stupanj zaštite	IP40
Način montaže	Stropna nadgradna
Min. temperatura okoline (°C)	-5
Maks. temperatura okoline (°C)	40
AA Klasa E 8101	AA4
Proizvođač	Schrack

Dimensions (mm)

NLWX...



Tablica artikla

OPIS	KAT. BROJ
design WX LED 1h/3h/8h odabir autonomije, stropna	
Ceiling surface mounting or optional chain rope or pendant mounting, 1h/3h/8h adjustable; pictograms with arrows left, down, up NLWXD003SC are already mounted, viewing distance: 90m	
Dodatni pribor	
Ovjes lanci komplet za svjetiljke tip WG/WX	NLWKO
Par cijevnih nosača 500mm, kromirani, montaža strop	NL1PV
Baterija 4,8V 2,0Ah za svjet. sa vl. nap. LED sa LPU modulom	NLAKKU4820
LPU or LEM module	